Solid State Energy Conversion Alliance



Workshop Proceedings

June 1-2, 2000 • Baltimore, Maryland







Pacific Northwest National Laboratory

Operated by Battelle for the U.S. Department of Energy



U.S. Department of Energy



National Energy Technology Laboratory

August 2000

Dear SECA Workshop Participant:

The National Energy Technology Laboratory (NETL) and the Pacific Northwest National Laboratory (PNNL) are pleased to provide the proceedings of the Solid State Energy Conversion Alliance (SECA) Workshop held on June 1-2, 2000 in Baltimore. The package includes the presentations made during the workshop, a transcript of the Question and Answer session, additional discussion concerning intellectual property, and the breakout session results that were developed for materials and manufacturing, fuel processing, modeling and simulation, power electronics, and thermal systems. We have attempted to accurately capture all the ideas and comments expressed during the workshop. A list of participants is also included. If you note any omissions or wish to provide additional information, we welcome your comments.

We are analyzing these results and developing the industrial team solicitation. Our current plan is to hold the solicitation open for three years with an opportunity to propose once each year. This will allow both a longer period for formation of teams and the addition of teams corresponding to the available budget and the addition of more government co-sponsors. We hope that all stakeholder groups will use the enclosed information in their planning endeavors as well. In order to permit careful review of the Workshop results and to consider other input, the date for issuing the solicitation for public comment is now mid-to-late August. Further details and updates will be available at the NETL website: www.netl.doe.gov.

We sincerely appreciate your active participation in the workshop and the breakout work sessions. Over 170 participants from more than 100 organizations representing various stakeholders groups provided a wealth of information and opinions. This collaboration among stakeholders groups will undoubtedly accelerate the planning for and the ultimate realization of SECA.

The tentative date for the next SECA workshop is April 2nd and 3rd 2001 in the Washington DC area. We look forward to your future participation in SECA.

Sincerely,

Wayne A. Surdoval SECA Project Manager

Solid State Energy Conversion Alliance (SECA)

WORKSHOP PROCEEDINGS

June 1-2, 2000 The Holiday Inn Inner Harbor Baltimore, Maryland



EXECUTIVE SUMMARY

The National Energy Technology Laboratory (NETL) and the Pacific Northwest National Laboratory (PNNL) hosted the Solid State Energy Conversion Alliance (SECA) workshop on June 1-2, 2000 to gather stakeholder input on the opportunities and challenges for achieving the goal of low-cost, broadly marketable fuel cells by 2010. These workshop proceedings include all of the speaker presentations, question and answer (Q&A) documentation, a discussion of the intellectual property issues, and two appendices for the breakout session results and the participant list. The Department of Energy (DOE) will use the breakout group results from the workshop as input to the preparation of technology plans and program solicitations to implement SECA. The proceedings will also be made publicly available.

Background

SECA is envisioned as a collaboration of government agencies, industry, universities, and national laboratories committed to the development of low-cost, high power density, solid-oxide fuel cells for a broad range of applications. Industrial teams, research and development performers, and funding organizations are part of the alliance. SECA has been formed to both accelerate the development of the industrial base needed to commercially produce low-cost solid-oxide fuel cells and to provide a core research program to provide any advancements necessary to achieving the aggressive SECA goals. The two host laboratories, NETL and PNNL, are the driving force behind SECA, providing the leadership, focus, and integration needed to bring solid-oxide fuel cell technology into near-term markets.

A Vision for Fuel Cells in 2010

Low-cost, high-efficiency, solid-state fuel cell systems will be available at less than \$400/kW for stationary, transportation, and military applications. This breakthrough will allow widespread penetration into these high-volume markets, ultimately leading to application of advanced fuel cell technology in "Vision 21" central-station power plants. The inherently high efficiencies of these solid-oxide fuel cells will provide significantly reduced CO_2 emissions and negligible emissions of other pollutants.

The basic building block will be a nominally 5 kW solid-oxide fuel cell module that can be mass-produced and used for residential, mobile, or military applications. For applications with larger power needs, the mass-produced core modules will be interconnected much like batteries, thus eliminating the need for custom designed fuel cell stacks to meet a specific power rating. SECA technology will ultimately lead to megawatt size configurations for commercial/light industrial packages and "Vision 21" central-station power applications.

SECA Proceedings i June 2000

Workshop Breakout Sessions

Seven breakout sessions were held:

- Materials and Manufacturing Session A
- Materials and Manufacturing Session B
- Fuel Processing Session A
- Fuel Processing Session B
- Modeling and Simulation
- Power Electronics
- Thermal Systems

Through a series of breakout group sessions, over 120 participants collaboratively addressed the following questions:

- What are the scientific and technology issues that exist for achieving the SECA vision by 2010?
- What are the research and development (R&D) opportunities?
- What engineering, development, and research actions are required to address the identified issues and opportunities?

The following definitions were used to characterize the maturity of the different components of the solid-oxide fuel cell technology identified in the breakout sessions:

- Engineering: something that has not been done before but can be solved by existing engineering procedures,
- Development: something that requires development of methodologies or extensive data gathering but a path to solution is clear,
- Research: problem areas for which there is no clear path to success and require new approaches.

Workshop Breakout Sessions Results

For each session, a summary is provided in Appendix A along with the "storyboard" results for issues; R&D opportunities; engineering, development, and research actions needed for implementation; and group "report-outs." Every effort has been made to represent the results of the consensus voting fairly and accurately without any individual influences or biases. Therefore, minimal narrative summary is provided since at some level a more extensive summary would represent an individual interpretation of the results. This results in a relatively "dry" report; however, it is one that we and hopefully others will find useful.

WORKSHOP PROCEEDINGS SOLID STATE ENERGY CONVERSION ALLIANCE WORKSHOP June 1-2, 2000

CONTENTS

Exec	:uti\	ve Summary	I		
l.	Presentations				
	A.	Fossil Energy Mission and the Fuel Cell Program	1		
	B.	Keynote Address: The Solid State Energy Conversion Alliance (SECA): Its Structure, Target Applications, and Role in DOE's Strategic Plan	5		
	C.	U.S. DOE, Office of Transportation Technology, Fuel Cells for Transportation Program Patrick Davis, Program Manager U.S. DOE, Energy Efficiency & Renewable Energy	22		
	D.	SECA: Transportation Applications	29		
	Ε.	Solid Oxide Fuel Cells and Department of Defense Applications Herbert Dobbs, National Automotive Center, TACOM	37		
	F.	Solid Oxide Fuel Cells and Stationary Applications	43		
	G.	Industry Presentations: Fuel Cell Markets 1. Carl Miller, Delphi Automotive System	.53 .61		
	Н.	SECA: Near-Term Program Opportunities	72		
II.	SE	CA: Question and Answer Session	76		
III.	Intellectual Property Fact Sheet				

WORKSHOP PROCEEDINGS SOLID STATE ENERGY CONVERSION ALLIANCE WORKSHOP June 1-2, 2000

CONTENTS (CONTINUED)

APPENDICES

I. Materials and Manufacturing – Session A	A-2
II. Materials and Manufacturing – Session B	
III. Fuel Processing – Session A	A-18
IV. Fuel Processing – Session B	A-25
V. Modeling and Simulation	A-32
VI. Power Electronics	A-39
VII. Thermal Systems	A-4 <i>6</i>

I. Presentations

A. FOSSIL ENERGY MISSION AND THE FUEL CELL PROGRAM

George Rudins, Deputy Assistant Secretary for Coal and Power Systems U.S. DOE, Office of Fossil Energy

1. Introduction

- I'm pleased to be here at the Solid State Energy Conversion Alliance Workshop. I'd like to thank Rita Bajura, Director of the National Energy Technology Laboratory, for inviting me to speak about this exciting new DOE initiative.
- Later speakers will discuss in some detail the structure and applications of the Solid State Energy Conversion Alliance, or SECA. I would like to speak about SECA in a larger context: how it fits into the national energy strategy, and the goals and milestones of the fuel cell program.
- 2. Comprehensive National Energy Strategy
- The Comprehensive National Energy Strategy, issued in April 1998, set forth five common-sense goals for national energy policy:
 - ! Improving energy efficiency.
 - ! Ensuring reliability.
 - ! Promoting clean energy technologies.
 - ! Expanding energy choices.
 - ! Cooperating internationally on energy issues.
- Fuel cells, and SECA, help us meet all five of these important goals:
 - ! Fuel cells are highly efficient. With thermal recovery, the total efficiency of fuel cell systems could reach 85%.
 - ! Fuel cells promise to be one of the most reliable power generation technologies, if not the most reliable. They are now being used by hospitals, hotels, and telephone companies as part of critical uninterruptible power systems. SECA will result in distributed generation products that will further increase grid reliability and safety.
 - ! Fuel cells are clean. They generate no solid wastes, and have dramatically lower emissions of nitrogen compounds, particulates, and greenhouse gases.
 - ! Fuel cells expand energy choices. They can be used in both distributed and centralized configurations. They provide siting and fuel flexibility. They allow us to use our abundant fossil-fuel resources in an environmentally friendly way.

- ! Fuel cells address environmental issues of global concern, including emissions of greenhouse gases. They are well suited for developing countries without an existing energy infrastructure, and will help meet a growing worldwide demand for energy. SECA will be an internationally cooperative effort. Through the SECA Core Technology Program, we expect to cooperate with the European Union, and others.
- 3. Near-Term Distributed Generation Market
- Given fuel cells' strengths, the abundance of fossil-fuel resources, and the need for highly efficient, clean energy technologies, the Department of Energy has funded fuel cell research for over two decades.
- The current fuel cell program is aimed at the near-term distributed generation market. The near-term market includes premium power applications: computer centers, hospitals, and other facilities that must have a reliable supply of high-quality electricity and are willing to pay for it.
- The current FE fuel cell program, now in the last phase of development, has two parts:
 - ! development of molten carbonate fuel cell systems, by Fuel Cell Energy, and
 - ! development of tubular solid oxide fuel cell systems, by Siemens Westinghouse.
- The program's goals are:
 - ! Commercialization of solid oxide fuel cell and molten carbonate fuel cell power plants in the 200-kW to 3-MW range by 2003.
 - ! Costs of \$1,000 to \$1,500 per kilowatt.
 - ! Efficiencies of 50 to 60%.
 - ! To have at least 50 MW per year of U.S. molten carbonate fuel cell manufacturing capacity, and to have at least 30 MW per year of U.S. solid oxide fuel cell manufacturing capacity by 2003.
- The U.S. and European growth and replacement market for near-term distributed generation is expected to approach 10 GW per year over the next decade. Globally it is expected to be 20 GW per year.
- The near-term developers, Fuel Cell Energy and Siemens Westinghouse, have had impressive test performance, and each plans multiple demonstrations within the next few years. Collectively, they could be capturing 1 to 2 GW per year of the global market by the end of the decade.
- 4. The Mature Distributed Generation Market
- To penetrate the mature distributed generation market, lower cost fuel cells are required. Distributed generation technologies must have low introductory and installation costs, and they must be reliable.

• SECA, which Ms. Bajura will describe in more detail, is a mechanism to build and integrate the industry base for low-cost fuel cells to penetrate the mature distributed generation market. SECA will build an alliance of government agencies, commercial developers, universities, and national laboratories to develop solid oxide fuel cells with the capability for immediate commercial success. SECA will build on the great progress to date in developing fuel cells and will assure a dramatic reduction in fuel cell cost down to \$400/kW for stationary power applications, which in turn should guarantee a very large market share for fuel cells.

The alliance will provide a focal point, an "organizational center" for the development of

- ! stationary power applications,
- ! auxiliary power units for military applications, and
- ! auxiliary power units for transportation applications.
- All three applications will benefit from the free flow of leveraged fuel cell technology development.
 SECA's cost goal for stationary applications is \$400 per kilowatt by 2010. Long-term cost goals for military and transportation applications are \$50 to \$200 per kilowatt. Efficiencies for all applications will be greatly improved over current state-of-the art.
- The results of this program will also provide early low-cost power systems for mature distributed generation market applications, and will feed directly into the Vision 21 Fuel Cells Program.

5. Vision 21

- Fossil fuels currently provide 85% of global and U.S. energy supply. Even under a climate change scenario, we will need to use fossil energy well into the future. But we need to use it smarter. The goal of Vision 21 is to wring every possible bit of useful energy out of carbon-based feedstocks to produce energy products, while eliminating all environmental concerns regarding electricity generation, and doing so at comparative costs.
- The Vision 21 fuel cells segment will develop advanced fuel cell modules that would be integrated with other Vision 21 advanced technology modules, and would be tailored to meet specific market needs. Fuels cells are needed to obtain the 60% efficient coal-fueled and the 75% gas fueled Vision 21 power plants of the future.
- To reach these high efficiency targets, a hybridized, high-efficiency fuel cell is required. Getting the cost of the fuel cell power module to \$400 per kW is a key factor in deploying Vision 21 systems by 2015. If this can be done, fuel cell/turbine hybrids could replace turbines as the power block in integrated gasification combined-cycle applications.
- These highly efficient combined systems, in multi-megawatt sizes, would have no environmental impact outside their own footprint. The goal is to make these modules ready for use in integrated systems by 2015. This program segment will accept additional technology input from the SECA program segments as solid state fuel cells become available.

Fuel cells also have an advantage in Vision 21 sequestration applications. Fuel cells have inherently
high efficiency and can also be configured to produce concentrated CO2 streams. Under the recent
Vision 21 solicitation, Siemens Westinghouse received an award to reconfigure their tubular solid oxide
fuel cell to produce a concentrated CO2 stream for use in enhanced oil recovery and other
applications.

6. Conclusion

- Part of the Department of Energy's mission is "to foster a secure and reliable energy system that is environmentally and economically sustainable." Fuel cells, and SECA, will help us meet this challenge.
- Fuel cells, with their roots in the space program, have the potential to truly revolutionize power generation. SECA is a natural extension of the existing fuel cell program, a logical next step.
- Thank you for joining us as we take this step into the future.

B. KEYNOTE ADDRESS: THE SOLID STATE ENERGY CONVERSION ALLIANCE (SECA): ITS STRUCTURE, TARGET APPLICATIONS, AND ROLE IN DOE'S STRATEGIC PLAN

Rita A. Bajura, Director U.S. DOE, National Energy Technology Center

Slide 1 The Solid State Energy Conversion Alliance: A Paradigm Shift in Technology Development

Good morning. I'm pleased to be here. It is my privilege to present an overview of the Solid State Energy Conversion Alliance, or SECA. I will discuss:

- A vision for the future of fuel cells.
- What the SECA alliance is.
- The concept behind the alliance.
- The proposed structure of the alliance.
- Next steps to initiate the SECA program.

Slide 2

The Vision: Fuel Cells in 2010

Let me start by sharing a vision of the future, a vision of solid-state fuel cell systems in 2010.

- These systems will be low cost: \$400 per kilowatt in the multi-kilowatt size range, a remarkable accomplishment in this small size range. The price trajectory will be downward, such that a \$50 per kilowatt system for transportation applications is on the horizon.
- Fuel-to-end-use efficiencies will be high: nearly twice as high as today's conventional technologies, again a remarkable accomplishment in the multi-kilowatt size range. These high efficiencies translate to reduced greenhouse gas emissions.
- Given a fuel, there will be a fuel-cell system that can operate on it. Fuel cells will be able to operate on natural gas, gasoline, diesel fuel, landfill gas, hydrogen, and defense logistics fuels.

Early movers in the fuel-cell industry will have commercialized them as auxiliary power units for the nation's cars and trucks, distributed generation units for homes, and field power units for military operations.

Slide 3

The Vision: A Core Module for Multiple Applications

The core of this vision is a 5-kilowatt, low-cost, high power-density, solid-state fuel-cell stack. The core module measures approximately 4 by 4 by 12 inches. It can be mass produced because it can be used in multiple end-use markets. Because it is a standard core module, the cost to customize it for multiple markets is cheap.

This concept of "mass customization of common modules" eliminates the Catch-22 of commercialization:

- High-volume production is needed to reduce costs,
- but low costs are needed to create a large market.

The 5-kilowatt core modules can be combined (like batteries) for applications with larger power needs. This "building block" approach enables low-cost customization. This is the Gateway or Dell computer concept applied to fuel cells. Gateway and Dell keep personal computer costs low and meet the exact needs of their customers by applying using the concept of mass customization.

Ultimately, the SECA concept could lead to megawatt-size fuel-cell systems for commercial and industrial applications and Vision 21 energy plants.

This vision is achievable, but it will take a new approach to technology development.

Slide 4

SECA — Realizing the Vision

That approach is SECA – the Solid State Energy Conversion Alliance.

SECA is an alliance of

- industrial teams, who individually plan to commercialize solid-state fuel-cell systems;
- R&D organizations involved in solid-state activities; and
- government organizations, who provide funding.

SECA is a national program that provides a forum to bring these entities together. All are interested in low-cost, high power-density, solid-state fuel-cell systems for some application. All are committed to the concept of "mass customization" as the route to reducing costs.

The high power-density requirement of the SECA program is a critical driver for transportation applications. This sector presents some of the most challenging requirements for the use of fuel cells. For example, a 5-kilowatt unit for auxiliary power must fit into a volume of 50 liters. (The "unit" includes the stack, reformer, and all other balance-of-plant components.) The 5-kilowatt unit must also weigh less than 50 kilograms, and have a surface temperature less than 45 EC.

High power-density is not as critical for stationary applications. However, by addressing these challenging requirements for the transportation sector, stationary developers may be able to substantially reduce their costs. Over the course of this workshop, I invite your thoughts on these draft requirements for the transportation sector.

The SECA program develops an integrated strategy to address the technical barriers of solid-state fuel-cell systems. SECA also focuses research performers on the breakthrough technologies needed to achieve the program goals.

Two national labs coordinate the SECA program: the National Energy Technology Laboratory (NETL) and the Pacific Northwest National Laboratory (PNNL). They provide the leadership, focus, and integration needed to achieve the goals of the SECA program.

Slide 5 SECA Structure

SECA represents a new model for joint government and private-industry technology development. Through annual workshops such as this, interested stakeholders help develop program goals. This information flows — through the program managers at NETL and PNNL — to the project management at NETL. The project managers coordinate the activities of the Industry Integration Teams and the Core Technology Program.

Each of the vertical bars in the viewgraph represents one Industry Integration Team. Each team is developing a fuel-cell system that they intend to commercialize.

The Core Technology Program (lower left in the viewgraph) consists of a "patchwork quilt" of R&D performers. Their projects address crosscutting technical issues in solid-state fuel-cell systems.

The blue arrows show a "circular" relationship. The Industry Integration Teams communicate their technology development needs to the project managers. The project managers translate these needs into research topics for the Core Technology Program. Participants in the Core Technology Program develop solutions that are transferred back to the Industry Integration Teams.

Slide 6 SECA Industry Integration Teams

Each Industry Integration Team is developing the capability to commercialize a solid-state fuel-cell system. It can be for stationary and/or transportation and/or military applications.

The teams are independent. They compete with each other. However, all are committed to the concept of mass customization as a route to reducing the cost of fuel-cell systems.

These "vertical teams" are competitively selected and will receive funding from interested government organizations, such as DOE's Office of Fossil Energy (FE). Our hope is that DOE's Office of Energy Efficiency and Renewable Energy (EE), and various organizations in the Department of Defense (DOD) will also decide to fund a suite of Industry Integration Teams. We are discussing the possibility of shared

funding with EE and DOD, and are delighted that they are participating in this workshop.

FE is currently developing its first solicitation for Industry Integration Teams. Wayne Surdoval from NETL will discuss this solicitation later this morning. We anticipate that FE will fund two or three Industry Integration Teams as a result of this solicitation. Our hope is other funding organizations will join in this solicitation or issue their own solicitation(s). The number of Industry Integration Teams ultimately selected will depend on the number of government agencies sponsoring the SECA program and their level of commitment.

DOD's Tank Armament and Automotive Command (TACOM) may choose to issue a solicitation for a solid-state fuel-cell module for tanks or other military vehicles.

The SECA program has momentum! "Pre-SECA" R&D work is already underway. Three industry projects in our present program are on a "SECA pathway." They are the Delphi, Honeywell, and McDermott projects. You will hear presentations from these companies later this morning. These organizations are either under contract with us, have a CRADA with us, or have been competitively selected for an award under a previous solicitation. The three projects are likely to be absorbed into the SECA program as Industry Integration Teams.

These three plus an additional two or three give a total of five or six possible Industry Integration Teams funded by FE.

Slide 7 SECA Core Technology Program

R&D performers in the Core Technology Program address the crosscutting technology development needs of the Industry Integration Teams. R&D performers may be:

- universities,
- national labs,
- industry, and
- small businesses.

They will conduct basic and applied R&D. The list of technology development categories we think the R&D performers will need to address includes:

- fuel processing,
- manufacturing,
- controls and diagnostics,
- power electronics,
- modeling and simulation, and
- materials.

This list is draft. I invite workshop participants to tell us if we have the right list of R&D needs.

The projects in the Core Technology Program are competitively selected, and are supported by the same

government agencies that fund the Industry Integration Teams. The target funding split is 40 percent for the Core Technology Program and 60 percent for the Industry Integration Teams.

FE has pre-existing contracts and awards that are relevant to the Core Technology Program. For example, we have projects with the University of Utah and the University of Missouri, and materials work with Honeywell. Our intent is to absorb these projects into SECA.

As a side note, we are successfully using the research model outlined here in our gas turbine program. The Advanced Gas Turbine Research Program is establishing the scientific foundation for 21th century gas turbines. The program is industry driven and involves 95 universities in 37 states. Both FE and EE fund the program. Pre-competitive research areas are defined by an Industry Review Board — the gas turbine manufactures. The South Carolina Institute for Energy Studies coordinates the program for DOE.

Slide 8 Intellectual Property — Cornerstone of the Alliance

SECA's treatment of intellectual property is the cornerstone of the alliance. It is a pilot program. DOE hopes this pilot will become the model for other technology development programs.

In the SECA program, DOE anticipates that all members of the alliance will be granted rights to own any inventions they make under the program. The intellectual property (IP) rights of the Industry Integration Teams are complete. However, those of the Core Technology Program are slightly limited. Participants in the Core Technology Program must be willing to license their patented technologies to any of the Industry Integration Teams, within reasonable time limits and other constraints.

Why this approach to IP? The SECA concept is based on the development of a common fuel-cell core module. This common module is essential to reducing the cost. The core module will be expedited <u>if</u> the technologies developed in the Core Technology Program are available for licensing to the Industry Integration Teams. We believe the Industry Integration Teams will be more likely to identify research needs if they are assured that all solutions will be within reach. This intellectual property approach will open the doors to collaboration!

There are other advantages:

- Technologies developed in the Core Technology Program can be incorporated into any designs that will benefit from them not just into the designs of the highest bidder.
- Research performers in the Core Technology Program will have a ready market for their inventions.
 They will reap royalties if an Industry Integration Team commercializes a fuel-cell system with their invention.
- This intellectual property arrangement increases the value of a technology. If a technology is important, all of the Industrial Integration Teams will need it to remain competitive.

Slide 9

Solid-State — The Choice for the New Millennium

- I want to examine some underlying questions about the SECA concept. First: Why solid-state? Solid-state fuel cells have several potential advantages:
- Solid-state fuel cells have inherently high efficiencies up to 60 to 70 percent hydrocarbon-toelectric efficiency. Hybrid or staged systems can have efficiencies up to 80 percent.
- Their high temperature simplifies high-temperature reforming of hydrocarbon fuels. The reformer and the fuel cell can be coupled.
- Solid-state fuel cells have easier head management and simpler control systems.

They lend themselves to low-cost manufacturing.

Slide 10

SECA — Now is the Time

Why is now the time for SECA? Recent technology breakthroughs have set the stage for low-cost solid-state fuel cells. These breakthroughs include:

- Advances in thin-film manufacturing of solid-state materials; for example, tape casting and multi-layer ceramic processing.
- Innovations in planar designs, such as anode-supported electrolytes.
- Compact fuel-processing technology, such as micro-channel reforming.
- Low-cost invertors.
- Advances from related industries; for example, semiconductor manufacturing.

Market forces make it the right time for SECA. Deregulation is opening the door for distributed generation technologies like fuel cells — domestically and internationally. There is a growing demand for more electric power in the transportation sector.

The environmental spotlight is extending small-scale applications. The superb environmental performance of fuel cells makes them a leading contender for market share of small-size systems.

Slide 11

Status of the Market — **Stationary**

I would like to touch on the status of markets for solid-state fuel cells. Other speakers will discuss markets in more detail.

In the stationary market, there is a movement from central station to distributed power. This is the mainframe-to-personal-computer analogy. Customers want individual control and reliability. Penetrating the distributed generation market beyond niche markets applications will require costs at or below \$400 per

kilowatt. We need breakthrough technologies to reduce costs to this level. Environmental concerns are driving distributed generations toward very clean systems such as fuel cells.

Slide 12

Status of the Market — **Transportation**

In the transportation market, solid-state fuel cells offer the potential of low cost systems that can operate using the existing fuel infrastructure. These fuel cells offer both very high efficiencies and low emissions. Auxiliary power units for long-distance trucks may be an early market applications for solid-state fuel cells

Slide 13 Status of the Market — Military

In the military market, fuel logistics are critical. Fuels represents 70 percent of the weight of materials moved in a military logistical deployment. DOD needs high-efficiency power sources compatible with defense logistic fuels. Systems need to be quiet, rugged, and have low thermal signatures. Field power units may be one of the early market applications for fuel cells in the military. The navy's decisions to use electric drive on new ships increases the potential size of the market.

Slide 14 A Paradigm Shift

Predicting the future is an inexact art. There is a Chinese proverb that says: "He who lives by the crystal ball will die from eating broken glass." With that said, a book was published recently that gives a view of the future. It is called *The Long Boom, A Vision For the Coming Age of Prosperity*. The authors are Schwartz, Leyden, and Hyatt.

The book describes several scenarios that might take place in the first two decades of this century. One scenario is named after the title of the book — the Long Boom. It depicts an unprecedented period of continued economic growth and world peace. But it is very clean, high-tech economic growth. Three to four billion people in developing countries move to the middle class. They want very clean energy: clean cars, clean electricity. Distributed power generation takes off. It is the beginning of the hydrogen infrastructure. And fuel cells can play a major role in this scenario.

This is a scenario that many of us would love to see play out. But even in the less optimistic scenarios, fuel cells can begin to play a major role. I believe fuel cells represent a major shift in how we produce electricity and power and power. Using the buzz words, fuel cells represent a paradigm shift, or a disruptive technology that will change the market dramatically. SECA accelerates this paradigm shift. It starts with the end in mind. It capitalizes on industry's willingness to cooperate across traditional lines.

Slide 15 Public Benefits

As a result, the public benefits. When advanced, ultra-clean, fuel cells move from niche markets to widespread use:

- Their high efficiency will result in significantly reduced emissions.
- Grid stability and reliability will be enhanced.
- We will have the option of continuing to use our low-cost domestic energy resources in an environmentally friendly way. We will be "greener sooner" using fossil fuels.

Slide 16


Responding to the Needs of the Nation


Assistant Secretary for Fossil Energy Bob Gee noted that "mass customization of fuel-cell components for stationary, mobile, and military applications can lead to mass manufacturing and in turn, to much lower unit costs."


This approach, the SECA approach, helps the Department of Energy fulfill its mission "to foster a secure and reliable energy system that is environmentally and economically sustainable."

As a new business model, SECA provides "the break with traditional ways of thinking" that author Stephen Covey said is necessary to make significant technological breakthroughs. SECA responds to the needs of the nation by providing the means to commercialize clean, low-cost, solid-oxide fuel-cell technology.


Thank you.























Status of the Market Stationary



- Major market penetration requires cost < \$400/kW
- Breakthrough technologies needed to reduce costs
- Environmental concerns driving DG to very clean systems



2K- 5/0

Status of the Market Transportation



- Potentially low system costs operating on available fuels
- Adaptable to standard transportation fuels
- High efficiencies
- Low emissions



2K- 5/00


Status of the Market *Military*





- Requires high efficiency, low signature power systems
- Fuel logistics are critical
- Electric drives/field power increasingly important




2K- 5/00











C. U.S. DOE, OFFICE OF TRANSPORTATION TECHNOLOGY, FUEL CELLS FOR TRANSPORTATION PROGRAM

Patrick Davis, Program Manger U.S. DOE, Energy Efficiency & Renewable Energy







Projected Fuel Cell Vehicle Performance (PNGV-Class Series Hybrid)




Projected Mileage, MPG

	Gasoline Fueled_	_Hydrogen Fueled
Urban Fuel Economy	79	101
Highway Fuel Economy	97	128
Combined	86	111

Note: Based on NREL/ADVISOR system modeling using target fuel cell efficiencies.








Near-term: Fuel flexible fuel processor

Primary focus ⇒ Advanced petroleum-based fuel

➡ Methanol, Ethanol, Natural Gas




Long-term: Renewable hydrogen

Primary focus

On-board vehicle storage



Advanced fuel is "gasoline-like," facilitates on-board processing, and is compatible with existing infrastructure. Gas-to-liquids, methanol, and ethanol may be used as blending constituents.





Program is Focused on Technical Barriers



Fuel Cells

There are significant technical and economic reasons that will keep fuel cell vehicles from making significant market penetration for 10 years.

- Technical Barriers
 - Platinum Usage
 - Durability
 - Air Systems
 - Start-up
 - Fuel Infrastructure
 - Cost

- Economic Barriers
 - Competition from other technologies
 - Fuel Cell Cost
 - Economics of fuel introduction
 - Cost of fuel



Projects and Funding by Budget Category



Systems

- Plug Power/Epyx
- IFC
- Energy Partners, AlliedSignal

FY00: \$6.0M

• ANL

Fuel Processing

- NUVERA
- Hydrogen Burner
- McDermott
- Plug Power/UOP
- AlliedSignal
- Arcadis
- ANL, LANL, PNNL

FY00: \$17.0M

Stack Subsystem Components

- Energy Partners, AlliedSignal, IFC, Plug Power
- IGT, Electrochem
- 3M, SwRI/Gore, Foster-Miller
- Vairex, A.D. Little, AlliedSignal, Meruit
- Spectracorp
- LANL, LBNL

FY00: \$14.0M



Accomplishments



Systems

- •Demonstration of first gasoline to PEM experiment (1997), first 10kW gasoline system (1999).
- •IFC Hydrogen Sys.
- MeOH (GM)
 system led to Zafira
 demonstration



Fuel Processing

- Epyx gasoline fuel processors 50kW
- •PNNL microchannel steam reformer
- ANL autothermal catalyst development
- GM MeOH steam reforming.
- Los Alamos PROX.



Stack Subsystem Components

- Los Alamos low platinum electrode, reconfigured anode
- •Inst. Of Gas Tech. \$10/KW bipolar plate.
- Sensors and controls
- AlliedSignal stack demonstrated in JLG boomlift.





Office of Transportation Technologies Interest in Solid Oxide Fuel Cell Technology



- Applications of interest in transportation
 - Auxiliary Power for Heavy or Light Duty
 - Propulsion for Heavy Duty
- Recently completed study by Parsons Infrastructure and Technology indicates auxiliary power application particularly of interest.
- OTT will continue to investigate application of solidoxide fuel cell technology to transportation and support R&D where appropriate.

Barriers to transportation applications:

Heavy Duty - Cost, Maturity, Durability/Robustness Light Duty - Cost, Maturity, Start-up, Thermal Cycling



Summary



Fuel Cells

- PEM fuel cell technology leverages multiple applications to achieve significant benefits in energy efficiency.
- Major technical barriers exist that prevent the introduction of PEM technology into today's light duty transportation options.
- The Office of Transportation Technology Fuel Cell for Transportation program is addressing critical technical barriers.
- Solid Oxide technology may find a role in transportation applications, but, like PEM, has significant technical and economic barriers to overcome.

D. SECA: TRANSPORTATION APPLICATIONS

Donald P. McConnell, Associate Laboratory Director Pacific Northwest National Laboratory


Transportation Applications for Solid Oxide Fuel Cells - Auxiliary Power


June 1, 2000


Don McConnell
Corporate Senior Vice President
Associate Lab Director, Energy
Pacific Northwest National Lab

Battetle


U.S. Department of Energy Pacific Northwest National Laboratory









Automotive Auxiliary Power Market Drivers				
Peak Power Requirements	kW			
Electric suspension	12.0			
Heated windshield	2.5			
Electric valve control	2.4			
Electric power steering	1.3			
Anti-lock brakes systems	0.67			
Catalyst Heater	0.6			
Diesel direct Injection	0.47			
Electric coolant pump	0.3			
Compartment Fan	0.3			
Total Expanding Demand	20.5 kW			
Battetie	U.S. Department of Energ Pacific Northwest National Laboraton			







Mobile Electrical Power Generation

- Engine/Generator
 - Fuel Energy ->Mechanical Energy->Electrical Energy
 - Low overall efficiency = 12-17% peak, 5-7% idle
 - Inexpensive & reliable
- Potential of Fuel Cells
 - Fuel Energy -> Electrical Energy
 - High overall system efficiency > 40 %
 - Expensive, unreliable and (as yet) unproven
 - Environmentally friendly, reduced emissions
- Fuel Cell Combined with Heat Pump
 - Overall system efficiency >65%
 - Full independence of auxiliaries from engine operation
 - Minimizes emissions from auxiliaries

Battetie

U.S. Department of Energy Pacific Northwest National Laboratory

Advantages of Fuel Cell for Auxiliary Power

- Electricity without combustion
- Continuous production of electricity as long as fuel is supplied
- Environmentally clean
- High efficiency, > 60 % stack efficiencies
- Low Noise
- Modular and compact
- Potential for low cost

Battetle

U.S. Department of Energy Pacific Northwest National Laboratory

"Generic" Automotive APU Specification

Power 5 kW net Rated voltage 42 Vdc

Mass Target < 50 kg (0.1 kW/kg)
Volume Target < 50 liter (0.1kW/liter)

Operation life >5000 hrs
Cold Start Required >3000 times

Warm Starts Required SOFC < 10 minutes
Maintenance Required >> 1000 hrs (30 ppm S)

Efficiency > 40 %

Surface Temperature < 45 degrees celsius

Baffelle U.S. Department of Energy Pacific Northwest National Laboratory

High Efficiency, Low Cost APU System

R&D Advances Required in:

- Solid Oxide Fuel Cell Stack
- Fuel Reformation
- Integrated Balance-of-Plant
- Thermal Control Subsystem
- Waste Energy Recovery Subsystem
- Power Electronics and Energy Storage Subsystem
- Entire System Cost must be driven down

Battetle

U.S. Department of Energy Pacific Northwest National Laboratory

Potential APU Markets Luxury Vehicles Recreational Vehicles Heavy Duty Trucks Short Haul Trucks Passenger Vehicles U.S. Department of Energy Pacific Northwest National Laboratory

E. SOLID OXIDE FUEL CELLS AND DEPARTMENT OF DEFENSE APPLICATIONS

Herbert Dobbs, National Automotive Center, TACOM







Solid Oxide Fuel Cells and Defense Applications

Solid State Energy Conversion Alliance (SECA)
Workshop

1 June, 2000

Herbert H. Dobbs, Jr.
Team Leader, Alternative Fuels and Fuel Cells
TACOM National Automotive Center

Tank-automotive & Armaments COMmand



SOFC's and Defense Applications Outline



- Armed Services Interests
- Fuel The sulfur problem
- Efficiency A key logistic issue
- PEM versus SOFC
- A way forward in ground vehicles
- Wrap up

As of: 1 June 00

Committed to Excellence



SOFC's and Defense Applications



Military Fuel Cell Applications

- Navy
 - Ship service power
 - Ship Propulsion
- Air Force
 - Bare Base tent city power
 - Flight line generator replacement
- Army and Marines
 - Ground vehicle APUs and propulsion
 - Mobile Generators
 - Soldier Power

As of: 1 June 00

Committed to Excellence

0./



SOFC's and Defense Applications



Fuel - The sulfur problem

- Navy
 - Ship fuel allows up to 10,000 ppm sulfur
 - JP-5 jet fuel allows up to 4,000 ppm
- Air Force and Ground Forces
 - JP-8 is the single peacetime and battlefield fuel
 - 3,000 ppm S limit
- Overseas fuels can have very high sulfur levels
- Historically low JP-5/8 sulfur levels are increasing

As of: 1 June 00

Committed to Excellence



SOFC's and Defense Applications



Efficiency and Emissions

- The U.S. has moved from forward basing to force projection
- Logistic support structures must be kept small
 - Less vulnerable supply systems
 - Faster to deploy
 - Less expensive in peace or war
- 70% of the Army's bulk supply burden is fuel
- Emissions are a real military concern
 - Most military activity is peacetime
 - Military trucks are affected now ships and aircraft later

As of: 1 June 00

Committed to Excellence

- /



SOFC's and Defense Applications



PEM: Advantages and Issues

- Advantages
 - PEM fuel cells are available
 - Good efficiency
 - High rate of commercial investment in PEM technology
- Issues
 - Difficult cooling in high ambient temperature
 - Noble metal catalysts cost and scarcity
 - Complex reformer
 - · Poor sulfur tolerance
 - Must remove carbon monoxide
 - · Penalizes efficiency and power density

As of: 1 June 00

Committed to Excellence



SOFC's and Defense Applications



SOFC: Advantages and Issues

- Advantages
 - Excellent integration with simplified reformer
 - Potential efficiency of combined cycle
 - Heat rejection is much easier
 - Promotes high power density propulsion systems
 - · Long term military vehicle propulsion candidate
- Issues
 - Much less mature than PEM
 - Scale up to large vehicle systems
 - Slow startup

As of: 1 June 00

Committed to Excellence

7/



SOFC's and Defense Applications



A Way Forward in Ground Vehicles

- SOFCs offer excellent features for future heavy vehicles, especially military vehicles
- Commercial success of SOFCs is the key to broad military adoption
- Long haul truck Auxiliary Power Units (APUs) are a major commercial entry point for SOFCs
 - Solution to anti-idling restrictions
 - Support for separately-powered engine accessories
- The APU builds the base for SOFC engines

As of: 1 June 00

Committed to Excellence



SOFC's and Defense Applications CONTACT



Herbert Dobbs, Jr.

Mailing Address:

U.S. Army TACOM National Automotive Center AMSTA-TR-N/272 (Dobbs) Warren, MI 48397-5000

(810) 574-4228 (voice) (810) 574-4224 (fax)

dobbsh@tacom.army.mil

As of: 1 June 00

Committed to Excellence

F. SOLID OXIDE FUEL CELLS AND STATIONARY APPLICATIONS W. Peter Teagan, Arthur D. Little, Inc.

Arthur D Little

Solid Oxide Fuel Cells and Stationary Applications

Presentation to: Solid State Energy Conversion Alliance (SECA)

June 1-2, 2000 Baltimore, MD Arthur D. Little, Inc. Acorn Park Cambridge, Massachusetts 02140-2390 U.S.A.

Peter Teagan Johannes Thijssen Sean Casten

Table of Contents

- 1 Market Segments Identification and Requirements
- 2 Market Drivers
- 3 Special Issues for SOFC Applications

Arthur D Little

June 2000

CAM STC/SECA.ppt

SECA 2000 Market Segments Requirements Several distinct markets exist for stationary SOFC generators, each with distinct characteristics and requirements. Highly variable power requirements
 High competing price of power (¢/kWh basis)
 Highest requirements for reliability and ease-of-installation
 CHP is difficult Residential Peaky power requirements
 Baseload or peak-shaving applications are possible, depending upon rate structures. Commercial CHP potential exists in some applications.
 "Premium" power credit can increase the value of on-site generators. Increased likelihood of dedicated loads High demand charges in some applications will favor peak-shaving systems.
 CHP potential exists in many applications.
 "Premium" power credit can increase the value of on-site generators. Industrial

Grid-support

• Can be installed to offset T&D and new generation capacity investments
• Implies that system is dispatchable by the local utility or ISO
• Most attractive for high efficiency systems, where the marginal cost of power is competitive with wholesale rates (1 - 4 ¢/kWh).

Arthur D Little

June 2000

CAM STC/SECA.ppt

SECA 2000 Market Segment Requirements

Performance and cost requirements for distributed generators vary by market segment.

	Stationary				Transportation		
	Build	dings		Utility		Automotive	Heavy Duty
	Residential	Commercial	maasma	Distributed	Central	Automotive	neavy Duty
1. Capacity (kW)	1 -5	20 - 500	200 - 2000	500 - 5000	>100,000	30 - 90	60 - 2000
2. Efficiency %1	>35	>35	>40	>40	>55	>40	>40
3. Life (years)	>10	>10	>15	20	20	0.5 3	2 - 10 ³
4. O&M (hours)	>4000	>1000	ongoing	ongoing	ongoing	>200	>200
Heat Recovery Temperature Level	Important 80 - 220° F	Important 80 - 250° F	Important a. 120 - 300° F b. 80 - 220° F	Not Important N.A.	Not Important N.A.	Not Important N.A.	Not Important N.A.
6. Cyclability	Important	Important	Not Important	Important	Not Important	Very Important	Important
7. Emissions ² NOx (ppm)	<20	<20	~150	~50	~150	~ 50	~50
8. StartupTime	Important⁴	Important4	Important⁴	Not Important	Not Important	Very Important	Very Important

Electric generation only, in cogeneration applications combinedelectric-thermal efficiencies approach 85%.

2 Varies by application and region; estimates reflect trends toward increasingly stringent regulations.


3 Actual operating time of the power system (not vehicle life).

4 Importance depends upon operation strategy. Peak-shaving units will require rapid startup, but base-loaded systems will not.

Arthur D Little

June 2000

CAM STC/SECA.ppt



SECA 2000 Market Segment Requirements

These analyses have shown that distributed generation technologies could generate economic value at installed costs of \$2,500 and below.

			Allowable Instal	ed Cost ¹ (\$/kW)
	Market Segment	Typical Capacity	Entry ²	Sustained ²
•	Commercial Cogeneration	50 kW - 2 MW	\$1,500 - 2,000	\$800 - 1,300
On-site	Industrial Cogeneration	5 - 200 MW	\$1,000 - 1,200	\$800 - 1,000
	Residential Power	0.5 - 10 kW	\$1,000 - 2,500	\$800 - 1,000
Utility	Distributed Power	5 - 20 MW	\$1,300 - 1,500	\$800 - 1,300
Uti	Central Station	100 - 500 MW	\$900 - 1,100	\$700 - 900

¹ Total installed system costs, including all owners costs. Targets apply widely to industrialized country markets. Costs have be en calculated based on a range of electricity and gas rate structures. Allowable costs for hydrogen fueled systems would be considerably lower as merchant hydrogen prices are typically 2-3 limes as high as natural gas.
² "Entry" costs are based on early high value markets. "Sustained" costs must be realized to achieve significant market penetration

Note that these costs do not include "premium" power benefits, which might increase the allowable costs by 25% or more above the values shown here (in selected applications).

Arthur D Little June 2000 CAM STC/SECA.ppt 5

SECA 2000 Market Segment Requirements

Residential applications have potential "mass markets", but pose unique technical and cost challenges.

- Electric load profiles are highly variable:
 - Peaks are ~ 10 kW in many homes
 - Baseload is often 0.1 kW or less
 - Average loads can be quite small, ~ 0.5 1.5 kW
 - ⇒ The most cost-effective on-site generators will be small, baseloaded architectures, provided that they can operate in parallel with the utility grid.
- From the home owners perspective, the generator must "look" like a typical appliance.
 - Minimal installation requirements
 - Minimal service requirements (once per year maximum)
 - Long operating life
- Little coincidence between thermal and electric loads in many US markets, making CHP difficult.
- Unresolved (but certainly challenging) codes and standards issues relating to onsite generators and onsite hydrogen flows, even as dilute H₂.


Arthur D Little


June 2000

CAM STC/SECA.pp

SECA 2000 Market Segment Requirements

Commercial building load curves present unique challenges and opportunities for distributed generators.





- Variation in peak and baseload power demand impact multiple generator specifications, including:
 - Capacity factor of load-following systems
 - Opportunities for demand charge reduction
 - Optimal product sizing strategy
 - Turndown requirements

Artiur D Little

June 2000

CAM STC/SECA.ppt

SECA Proceedings 47 June 2000

SECA 2000 Market Segment Requirements

Significant markets exist for generators with rated capacities greater than 10 kW (e.g., non-residential units).

Building Type	Baseload Power Requirements (kW)	% of US Commercial Electricity Use (kWh)
Large High-Rise Office Largest Hospitals Largest Hotels Large Shopping Mall	1,000+	20%
Hospitals (200 - 300 beds) Large Hotels (750 rooms) Office (200,000 sq. ft.) School (125,000 sq. ft.) Large Retail	200 - 1,000	35%
Office (50,000 sq. ft.) Average Hotel (75,000 sq. ft., 125 rm) Multi-family (100 units)	50 - 200	35%
Fast Food Restaurant (4,000 sq. ft.) Small Office Building (10,000 sq. ft.) Multi-family (<25 units)	10 - 50	10%

^{*}Peak loads can be 2-3 times higher.

However, large numbers of potential kWh sales do not necessarily imply large numbers of unit sales!

Artiur D Little

June 2000

CAM STC/SECA.ppt

Table of Contents

- 1 Market Segments Identification and Requirements
- 2 Market Drivers
- 3 Special Issues for SOFC Applications

Arthur D Little

June 2000

CAM STC/SECA.ppt

SECA 2000 Market Drivers

As the energy industry deregulates, market drivers for stationary power generation are rapidly changing.

Energy Costs Matter!

- Technologies that can successfully compete with the grid on a ¢/kWh basis can bring value to the end user.
- However, prevailing costs may not be the best indicator of economics:
 - Utilities may adjust their rate strucutres in light of competition from on-site generators
 - Electricity rates are falling in the wake of deregulation.
- Even if the marginal cost of power generation is high, on-site generators may still be able to bring about value through demand charge (\$/kW) reduction.
- Energy cost savings can be a powerful (but complex!) driver for on-site power generation.

Some power is "premium"

- Growing distribution of electronic devices is increasing users' sensitivity to minor variations in power quality and/or reliability
- and/or reliability.
 For many users, the cost of a power outage is substantially larger than the cost of power
 - Credit-card processing centers
 - Internet servers
 - Brokerage housesetc.
- Deregulation does not necessarily provide for gridreliability, thus raising uncertainties in the future.
- There is an increasing focus on "point-of-use" solutions to power quality issues.

Who will own the generator?

- Electricity users could own the generator
 - This allows for the full realization of energy cost savings.
- However, it is beyond the "core business" of many end users.
 Gas/electric utilities could own
- Gas/electric utilities could own the generator
 This allows for the full
 - This allows for the full realization of infrastructure cost savings (avoided T&D costs. etc.)
- costs, etc.)

 Third parties are starting to play a role in DG
 - ESCOs
 - etc.
- Ownership structures will affect the economic and operating requirements of all distributed generators.

Arthur D Little

June 2000

CAM STC/SECA.ppt

10

Table of Contents

1 Market Segments Identification and Requirements

2 Market Drivers

Special Issues for SOFC Applications

Artiur D Little

June 2000

CAM STC/SECA.ppt

SECA 2000 Special Issues for SOFC Applications


SOFC has attractive characteristics for many (not necessarily all) stationary power applications.

- Heat recovery potential:
 - Can interface with most industrial and commercial thermal needs
 - Allows for operation of multi-effect absorption cooling technology.
- Electric Conversion Efficiency:
 - Allows for higher "allowable costs" than lower efficiency options
 - Higher efficiency can decouple the economics from the need for heat recovery.
- Fuel processing simplicity:
 - Reduces risk and cost of technology.

Arthur D Little

June 2000

CAM STC/SECA.ppt



SECA 2000 Special Issues for SOFC Applications

There are several issues which require quantification to better understand the application range of SOFCs.


- · Thermal losses:
 - At what combination of operating characteristics (capacity factor) and rated capacity do thermal losses become unacceptable? (see next slide)
- Cyclic operation:
 - Can the system be shut off (for example, during periods of low or zero loads)?
 - How many cold start cycles are acceptable? How can the system be designed to minimize fatigue factors relating from thermal expansion/contraction?
 - What are the losses during "idle" periods, and how can they be minimized?
- · Start-up time:
 - How fast can the system be started?
 - How should it be maintained (e.g. at what temperature) when idle?

The above issues become increasingly important in lower capacity ranges associated with residential and light commercial service.

Arthur D Little

June 2000


CAM STC/SECA.ppt



G. Industry Presentations: Fuel Cell Markets

Carl Miller, Delphi Automotive Systems
 Nguyen Q. Minh, Honeywell
 William P. Schweizer, McDermott Technology, Inc.








Mission



- Global Automotive Systems Supplier With Component Excellence
- Passionate Pursuit of Customer Satisfaction Through Technology, Quality, Cost, Responsiveness and Attitude
- Grow Revenue Across a Diversified Customer Base
- Increase Stakeholder Value Through Revenue Growth and Superior Returns
- Create an Environment Where Every Employee Can Contribute and Excel







Delphi Automotive Systems Core Competencies



- Chassis System Design and Integration
- Mechatronics-Electromechanical Integration
- Friction Management
- Fluid Power Management
- Value Enhancing Processing
- Energy Conversion
- Energy Storage
- Sensing & Actuation
- Exhaust & EVAP Emissions
- Fuel Delivery & Combustion Control




Delphi and BMW Announce Development of Fuel Cell


Auxiliary Power Unit.

For Release: April 26, 1999

MUNICH, Germany /PRNewswire/ --

Delphi Automotive Systems (NYSE: DPH) and BMW announced today that they have signed a development agreement to produce vehicles that use a solid-oxide fuel cell as an auxiliary power unit and that have the potential of being clean, high-power-generation vehicles. Under the development agreement, BMW and Delphi are jointly developing a fuel cell system that will be used as an auxiliary power unit for gasoline engines. This will allow BMW to offer more features more efficiently with the potential to reduce the emissions of an internal combustion engine.





Technical Challenges




SOFC has many challenges to be viable as an automotive technology:

- (1) Cost
- (2) Robustness (especially Thermal Cycling)
- (3) Anode oxidation sensitivity
- (4) Low Fuel Utilization
- (5) Thermal Management (high temperature insulation)
- (6) System integration (many new technologies)

But:

- SOFC is an attractive automotive fuel cell technology
- It has other future mechanizations which support the trend to nearly-zero toxic emissions and much reduced CO2 emissions



SOFC Cost development potential



Further development to achieve cost targets:

- Internal Reforming
 - simplification of thermal management, elimination of various balance of plant issues
- Thermal Control Subsystem
 - integration (internal reforming, adiabatic wall) and simplification
- Waste Energy Recovery Subsystem
 - simplification, possibly elimination
- Materials
 - potential to reduce stack material costs up to 80%
 - potential to use metal interconnects
- System operating temperature
 - lower system operating temperature leads to less expensive materials in balance of plant subsystems

Delphi interests



Delphi is interested in leveraging multiple applications (i.e. military, stationary, portable power and automotive) in the interest of <u>accelerating</u> technology development.

Three year goals



Fuel Cell Design and Manufacturing objectives

Operating Temperature: 750 to 800 °C
 Current Density (stack): 0.5 to 0.7 A/cm²
 Power Density (stack) 1.75 kW/L
 Normal Operating Voltage (cell) 0.7 to 0.8 V
 Stack Cross Section (cell) 15 x 15 cm
 Production Cost (stack) \$200 / kW

Priority R&D topics



SUBSYSTEMS / BALANCE OF PLANT

- validation and optimization of stack / reformer in automotive mechanization
- innovation of low cost, high performance high temperature heat exchangers
- cost effective and standardized electrochemical hardware
- robust low cost, high temperature sensors and actuators
- low cost, high performance insulation

MANUFACTURING - processes for high volume production


- integration: optimize total system for fewer and lower cost components
- reliable low-cost processing
- alternative seal designs
- simple, compact internal reformer

Honeywell

Honeywell Solid Oxide Fuel Cells Markets and Technology Status

Nguyen Minh Honeywell Engines & Systems Torrance, CA

> SECA Workshop Baltimore, MD June 1-2, 2000



Approaches to SOFC Technology


- Light weight and small size
- High performance
- Modularity
- Fuel flexibility
- Low-cost manufacturing and material

Honeywell


SECA Meeting June 1, 2000 SECA. ppt- 3

Low Cost Manufacturing Process

 Stack fabrication process with tape calendering





 Multilayer electronics fabrication process





SECA. ppt- 4


SECA Meeting June 1, 2000





















Concluding Remarks


- Honeywell has been developing low-cost, highperformance planar SOFC technology for a broad spectrum of power generation applications
- Honeywell has developed business plans and technology roadmaps to commercialize SOFC products


Honeywell

SECA Meeting June 1, 2000 SECA. ppt- 13
















H. SECA: NEAR-TERM PROGRAM OPPORTUNITIES

Wayne A. Surdoval, SECA Project Manager U.S. DOE, National Energy Technology Laboratory

SECA SOLICITATIONS

Near-Term Opportunities

Schedule

By Wayne Surdoval SECA Project Manager NETL





Near-Term Solicitations

- Two FY 2001 Solicitations
 - Industry Team Solicitation (60% of SECA budget)
 - Core Technology Program Solicitation (40% of SECA budget)
- Size of the SECA budget depends on FY 2001 Legislative support for Fuel Cell Technology.
 Not finalized till later in the summer



Industry Team Solicitation

- It is anticipated that two to three Industry Teams will be awarded in FY 2001 for a three year performance period.
- The primary deliverable will be a functioning prototype that meets the three year intermediate goals identified in the solicitation.
- Selection will be based on both Business and Technical criteria.
- It is anticipated that Cooperative Agreements will be awarded with 20% cost share for Phase I.



Core Technology Program Solicitation

- Selection Criteria will be more heavily weighted toward Technical considerations.
- Topics will be based on Industry Team needs. Periodic review meetings will be held.



Industry Team Solicitation Schedule

- July 14, 2000 Solicitation issued for Public Comment
- September 15, 2000 Solicitation posted in the Commerce Business Daily
- October 2, 2000 Solicitation issued
- December 15, 2000 Proposals due



Core Technology Program Solicitation Schedule

- April 16, 2001- Solicitation posted in the Commerce Business Daily
- May 1, 2001 Solicitation issued
- June15, 2001 Proposals due



II. SECA: QUESTION AND ANSWER SESSION

Joe Strakey: Thanks, Wayne. I'm sure you all have some questions about the program and about what Wayne just talked about, as well as intellectual property and things of that nature. So I'll ask our panelists to come up, and we're going to take some questions from the floor.

Mark [Williams], Lisa [Jarr], Gary McVay, I'm going to ask all of you to use the microphone so that everybody can hear. If we don't get to your questions, just fill out a slip of paper and drop it off at the registration desk, and we'll get back to you with answers as best we can. [Note: None were submitted.] There are still things that are not 100 percent defined, so you may not get the firm answer that you might like. If we do get stumped, we can always turn to our other participants in the program who may be able to answer some of the questions that we can't.

With the remaining time, we'll try to take some questions for the people who spoke this morning. As I mentioned before, we cut off questions so that we could keep to the schedule. So with that, would someone like to start it off?

By the way, before you start, I should mention the following. You know Wayne [Surdoval]. Mark Williams is the Product Manager for our Fuel Cells Program at NETL. Gary McVay is from PNNL, where he manages Materials Programs, and he's our SECA contact for this program. Lisa Jarr is one of our attorneys. She specializes in the intellectual property area and she has had much to do with the development of the "exceptional circumstance" that will provide for limited non-exclusive licensing within the SECA pilot-program.

Sy Ali (Rolls-Royce): Mr. Rudins mentioned he would like to see \$400 per kilowatt by 2010. The speakers indicated values for central power under \$700 to \$800 per kilowatt without indicating the date. When do they expect to get to \$400 per kilowatt?

Wayne Surdoval: The program right now is structured such that the \$400 per kilowatt goal is a 2010 goal. It's pretty clear that we will have three phases. Phase 1 and phase 2 will have less aggressive cost goals. However, they will be aggressive enough that we can clearly get into a broad market even at these initial goals.

Joe Strakey: Keep in mind that we're trying to get to large central station plants using solid oxide technology in the 2015-and-beyond time frame for Vision 21 applications.

Lyman Frost (INEEL): Could you speak a little bit more to the sharing of the intellectual property and how that is going to work?

Lisa Jarr: The vision of SECA was that it would be critical to have the technology developed by the Core Technology Program available to all of the Industrial Integration Teams. Because we are a Government agency, we are restricted by law in taking certain rights from small businesses and nonprofits, such as universities, unless there is an exceptional circumstance under which we feel that we need to do

that. We feel that this program represents such an exceptional circumstance. So we are going forward to get permission to require the Core Technology Program developers to offer to the Industrial Integration Teams a non-exclusive license, under reasonable terms and conditions, for any patented technology that they develop. This option would be available for a period of time — probably a year after a patent is issued — and the Industrial Integration Teams could express an interest in whether they would like to engage in negotiations for such a non-exclusive license. The negotiations would be between the patent owner and the Industry Integration Teams.

Joe Strakey: Let me add to that. There's an important connection between the Industrial Integration Teams and the crosscutting developers of the Core Technology Program. That is the Industrial Integration Teams have something to gain from the technology that's developed by the Core Technology Program. They can get a non-exclusive license to the technology, which otherwise they may not have access to. With the exception circumstance in place, it will be an incentive for the Industrial Integration Teams to act as a guiding body to give the Alliance ideas, through DOE, of what research is important and relevant to the industry teams. We think that's a very important connection, and we're going to proceed with getting that in place.

Lisa Jarr: Right. And the benefit to the core technology developers is that they have a group of licensees for their technology where they can reap some benefit back to their programs. We think it's a win-win situation for all involved.

Wayne Surdoval: We plan to put a substantial amount of the budget into the Core Technology Program because, in return, it does help the alliance. In terms of this program; focusing this program; keeping it focused; if this relatively minor intellectual property change in fact is available, it will be critical to keeping the program focused. Otherwise, there wouldn't be much motivation for all of the partic ipants in the program to work together.

Momtaz Mansour (ThermoChem): On intellectual property, unless you provide reciprocity, so that patent holders of enabling patents also have the right to license stack technology, then you're going to have a lot of litigation on your hands. If there's reciprocity in the program, there will be cooperation. But if you're going to make it such that technology invented somewhere in a small business has to end up in the hands of a bigger company, it's not going to fly.

Lisa Jarr: We're talking about non-exclusive rights.

Momtaz Mansour (ThermoChem): There's no such thing. Once you non-exclusively license the technology, it's lost its value. The other issue is: 18 to 20 years ago, the question was reduction in cost of the stack and the material cost. I remember the number; it was \$285 per kilowatt at that time for a solid oxide fuel cell, and the target was \$400 to \$500. What is new that we know now that allows this target to be real? What is it? Why is this costing so much? Is it the mass production, the lack of market? What is the issue?

Gary McVay: For the first time, we've got the type of industry interested in and committed to making solid oxide fuel systems that has the low-cost production capability for it to become a reality. I mean, that's what these folks, the suppliers to the auto industries, do for a living. So that's one of the new things. And the other thing is that we have a market pull. We have a customer saying "if you can do, we'll buy

it." We've got an order in place for it. And technology has moved along. We haven't stood still since the time you were talking about, and so we have better approaches to things. I think it's a combination of technology advancements and getting high-volume, low-cost producers involved.

Mark Williams: I would like to emphasize that there's been a tremendous amount of progress in the fuel cell industry in the last 18 years, witnessed by numerous scale-ups and improvement in materials and components.

Wayne Surdoval: Some other factors too: One thing we're emphasizing is high power-density design. If you could increase the power density by a factor of two, you can substantially reduce your stack cost by that alone. We have had a number of studies done. If you look at the material cost at the higher volumes of projected production; the more simple manufacturing methods applicable to flat ceramic plates such as tape casting and screen printing; and if metallic interconnects are viable, the cost numbers do come out to \$400 per kilowatt as a reasonable goal. We have several studies that show this.

Dave Archer (Carnegie Mellon): I guess I wanted to make a special plea for those of us intended to respond to your multi-level fuel cell fabrication proposal. We had hoped to respond to that, and we're told that a new program that you've announced today would be available. But it seems a rather long time to wait from now, when we had hoped to make a proposal to your multi-level fuel cell proposal, to the time when core support proposals will be entertained, approximately a year from now, I guess. A year's vacancy is a concern.

Wayne Surdoval: Today we are only speaking about the SECA program. There are other programs throughout DOE. There will be many opportunities. There are SBIR opportunities. There are opportunities through AR&TD [Advanced Research and Technology Development]. We actually have a solicitation on the books — it's written, and ready to be issued shortly — that would be directed to the universities. There will be other opportunities. This is strictly SECA. The SECA program will be an industry-driven program, but there will be other work. We also need to keep other work going to achieve the longer-term breakthroughs that can help us down the road.

Joe Strakey: Let me add that in the Government, the budget cycle is at least 2 years, so making a change in program direction is difficult, and we felt that it was important not to get people started in one direction and then change it once the contracts were awarded. So, with this slight delay, we pay a price, but I think in the long run it will provide additional opportunities for developers in this area, and will avoid early terminations or anything like that.

Gerry Agnew (Rolls-Royce): I'd like to return to an earlier topic and raise a question: What happens to the background IPR [intellectual property rights] for the existing stack development technology people who participate in this? And related to that is the question: For somebody who has the option to be in a vertical integration team or who has stack technology developed in-house, if we go in as a vertical integrator, are we just paying for the development programs that other people were involved in when we have a stack program of our own? How are you going to handle the background IPR for the core developers?

Lisa Jarr: The DOE intellectual property provisions will apply to any of these awards. And for large businesses, there is a background patent licensing requirement. It's never been invoked, that I'm aware

of, by the Government — at least not by the Fossil Energy program — but it is a statutory requirement. The large businesses will be able to apply for a patent waiver for any inventions that they make under this program. But there is a limited background patent license requirement for purposes of practicing technology developed under the Government-funded program, which in this case would be, I guess, a financial assistance award under SECA. It's something that we really cannot get away from. But as I mentioned, it has not been invoked in any program that I'm aware of.

Gerry Agnew (Rolls-Royce): That would imply then that you don't feel you're building substantially on the existing IPR — the older IPR will be new IPR.

Lisa Jarr: Well, I think the idea is not for us to do fuel cell development, but to help you folks do it. The reason that we would invoke a background patent license would be if you've done work for us under this program and basically put it on the shelf, and we would have somebody that comes to us and say "We want to practice that technology that you paid to have developed," and we need to have a background patent license from Rolls-Royce or someone else. The intention is that you're going to be off practicing this technology in the marketplace and that we're not going to have to get to that point.

Joe Strakey: If there's a market need for a technology that's not being satisfied because somebody is sitting on the invention, that's hard to imagine that's going to happen. I've heard a story that it happened once in DOD, but . . .

Lisa Jarr: Did you have another part to your question?

Joe Strakey: I didn't quite follow the second part.

Gerry Agnew (Rolls-Royce): Yes, the question really is: Will the vertical integrator effectively end up licensing technology that was developed before this program began?

Joe Strakey: Licensing it to core program?

Gerry Agnew (Rolls-Royce): Implicitly.

Lisa Jarr: You're looking at the risk to your existing intellectual property — is that the idea?

Gerry Agnew (Rolls-Royce): Well, essentially, for Rolls-Royce, if we join as a vertical integrator, we're effectively going to be climbing on the back of Honeywell or other people's development programs, and yet we have our own. So, what is the incentive for us to do that? We're just helping those guys in some ways. That's the question in my mind.

Joe Strakey: There's some confusion on this. Your intellectual property rights are the vertical developers' and wouldn't pass on to anyone else. You'd be building on what you've done before.

Joe Strakey: You mean in the horizontal teams?

Wayne Surdoval: Well you can certainly act as a n industrial integration team. I mean a single company can act as a vertical integrator if you can meet all the requirements that will be in the solicitation for a vertical team. I don't really see a conflict myself.

Joe Strakey: More concerned about being of the Core Technology Program?

Wayne Surdoval: Yes, a company can also be part of the Core Technology Program. But in that case, whatever the intellectual property requirements are, you've simply got to accept them. And, if you choose to do that, then you're part of the technology pool. I would fully expect that certain companies would develop intellectual property or technology in-house as part of an industrial team, as well as be interested in what's going on in the core program. The core program is more for breakthrough technology. I would not expect you to be part of the core program if you had a significant prior intellectual property position ready for licensing, and in order to work in the core technology program you had to divulge that. I would think you would keep that in the industry team. There's no reason why you couldn't. That's your choice.

Joe Strakey: Other questions? How are we doing on time here? Are there any quick questions for any of the speakers this morning? You have to come to the microphone.

Steve Visco (LBNL): I have a question. It's kind of an organizational question. It also ties into IP [intellectual property]. If you have these kind of integral, vertical teams, which are, say, self-contained, but they can license technology from these horizontal core technology teams, you've also got the issue of these horizontal teams working, I assume, with the various vertical teams. And there's always this problem of cross contamination. I mean, there's going to be some sensitivities, I would think. You've got a hot project going in a vertical team; you've got members from horizontal teams who are seeing everybody's technical problems and trying to solve them. How are you going to keep the barriers there? How's that done in terms of intellectual property and how these two teams work with one another on two sets of teams?

Wayne Surdoval: I think that's up to the participants. We recognize that cross contamination could exist. I think the national labs in particular deal with that all the time.

Joe Strakey: Let me add to that. I think that maybe there's some misperception. The idea is that the industry team would provide input to the Government. DOE would decide what topics should be pursued on the horizontal teams, and we would issue solicitations. So, it's not like the horizontal team members would be working daily with each one of several vertical developers. I think that probably solves it.

Steve Visco (LBNL): So you will have separation?

Wayne Surdoval: Yes. The core program will consist of very specific contracted pieces of work.

Joe Strakey: See, it goes through our project management. You've got industry input, which feeds through project management, and it keeps it separated that way. Okay, we got a couple more.

Lyman Frost (INEEL): Let me ask one more question, following up on what you've just said. Underneath Federal law, the national labs are not allowed to work exclusively with any particular company. They have to be able to go to any of a number of companies if they want that area of

expertise. Are we going to be able to work exclusively with industrial companies to protect their technology base in this area?

Lisa Jarr: Maybe I don't follow completely the restriction on the national labs, but I think . . . you're talking about in the core development program now?

Lyman Frost (INEEL): Yes, in the core development team, if more than one company wants to work with you in a particular area of technology, you have to be willing to work with each one of those equally. So the question I have is: If we were working on one of the core teams, would we be able to work exclusively with an industrial team in a particular area of technology?

Wayne Surdoval: I think in the core program, assuming things go as planned, you would almost by definition be working for everybody.

Joe Strakey: For the public, yes.

Wayne Surdoval: Now, in the other sense, if you wanted to establish a CRADA with a specific company, within the rules of establishing a CRADA, that would also be acceptable.

Lisa Jarr: I think, in that case, you probably would be talking about working with one of the industry integration teams versus the core program. Then, whatever rules and restrictions fall from contracting or doing CRADAs with a certain company would apply. We anticipated . . . and we've had national labs as subcontractors or team members on these teams before . . . and we anticipate that that could happen under these industry integration teams also.

Gary McVay: Almost by definition, when you're working on a core team problem, you're working with all of the industries. They all are interested in the solution of that problem and will receive the output of that research.

Joe Strakey: Just like any national lab project now. I don't see any difference except for this one of intellectual property.

Joe Strakey: Last one before lunch.

Ismail Celik (WVU): I am from the University. I see one component missing from the SECA program. That's the education of the engineering students for supplying the demand for this mass production and maintenance and all these . . .10, 20, maybe 30 to 50 years. How do you envision supplying this demand without a program in curriculum development in solid oxide fuel cell technology or in general fuel cell technology?

Wayne Surdoval: We're working on that now. As I said, the SECA program certainly encompasses universities. And when you encompass universities, typically you are training grad students. At the same time, we have other solicitations available. There is one that is not on the street quite yet, but when you read it, it is specifically written to enhance educational opportunities and support graduate student training for solid oxide fuel cell work. Again, there are other funding avenues besides SECA. This is strictly SECA. This is a very short-term industry driven program.

Joe Strakey: I'm going to have to cut it off because were running late.

III. INTELLECTUAL PROPERTY FACT SHEET EXCEPTIONAL CIRCUMSTANCES FOR WORK PROPOSED UNDER THE SOLID STATE ENERGY CONVERSION ALLIANCE (SECA) PILOT PROGRAM

An Exceptional Circumstance determination is required to implement a slightly modified intellectual property agreement (relative to the Department of Energy Acquisition Regulations (DEAR)) in contractual or financial assistance arrangements with members of the Solid State Energy Conversion Alliance (SECA) Core Technology Program (universities, National Laboratories and other research-oriented programs). This modification of the standard DEAR intellectual property agreement is critical to the SECA structure and the implementation of the program. SECA is regarded as a pilot-program demonstrating a new Department of Energy (DOE) business model. Without this modification this pilot-program could not be implemented in a significant way. A brief description of SECA and the modified intellectual property agreement is discussed in the following paragraphs. DOE does not intend to modify any existing practices with regard to background rights. The purpose of SECA is to focus significant resources on a well defined technology target that in DOE's judgment has broad applicability. DOE believes the Exceptional Circumstance will ensure that the individual research organizations that receive substantial resources from the SECA budget will benefit both the Alliance and themselves. If the Exceptional Circumstance were not implemented, the majority of funding available for research would most likely be funneled through the industrial concerns at their discretion as it has been in the past.

The statutory authority for the Exceptional Circumstance follows. The implementation of this Exceptional Circumstance determination will further the goals of 35 U.S.C. § 200, e.g., to promote collaboration between commercial concerns, and nonprofit organizations and small businesses. Exceptional circumstance determinations are authorized by 35 U.S.C. § 202(a) when the agency determines that restricting of the right to retain title to an invention resulting from federal sponsored research and development "will better promote the policy and objectives of this chapter." This Exceptional Circumstance determination will better promote the following policy and objective of the Congress as described in 35 U.S.C. § 200: to use the patent system to promote the utilization of inventions arising from federally supported research or development; to promote collaboration between commercial concerns and nonprofit organizations, including universities; to ensure that inventions made by nonprofit organizations and small business firms are used in a manner to promote free competition and enterprise; and to promote the commercialization and public availability of inventions made in the United States by United States industry and labor.

The DOE is exploring a new business model by implementing the SECA Pilot Program through the National Energy Technology Laboratory (NETL) in partnership with the Pacific Northwest National Laboratory to develop solid-oxide fuel cell technology for a broad range of applications. The major element of the pilot program is the development of highly efficient, cost-effective and mass-producible solid-oxide fuel cell systems. The SECA goal is to enable the implementation of the mass-customization approach developed by U.S. Industry to solid-oxide fuel cell technology. This program offers the prospect of improving the overall efficiency of power generation by a factor of two over traditional technologies and

with greatly reduced emissions. These solid-oxide fuel cell systems have also been identified as one of the key enabling technologies for achieving the efficiency goals in DOE's Vision 21 Program.

The SECA will be structured into Industrial Teams and a Core Technology Program (an applied research and development program consisting of universities, National Laboratories, and other research-oriented organizations). A NETL led project management team will maintain responsibility for both of these activities. The Industrial Teams will develop the fuel cell stack, system, and manufacturing capability and the packaging needed for different markets; the number of teams will depend on the level of commitments from sponsors. The Core Technology Program will be focused on finding solutions to the more difficult shared technical barriers in support of the Industrial Teams.

In brief, the proposed intellectual property agreement will require members of the SECA Core Technology Program to offer to each of the Industrial Teams the first option to enter into a non-exclusive license upon terms that are reasonable under the circumstances, including royalties, for subject inventions developed under the SECA program. The field of use of the license could be limited to solid-oxide fuel cell applications, although greater rights could be offered at the discretion of the invention owner. The offer must be held open for at least 2 years after the U.S. patent issues and the invention owner must agree to negotiate in good faith with any and all Industrial Teams that indicate a desire to obtain at least a nonexclusive license. Exclusive licensing may be considered if only one Industrial Team expresses an interest in licensing the invention. Partially exclusive licenses in a defined field of use may be granted to an Industrial Team, as long as doing so would not preclude any other Industrial Team that indicates a desire to license the invention from being granted at least a non-exclusive license for solid-oxide fuel cell applications. The Core Technology Program participant that owns or controls the invention must enter into good faith negotiations with the individual Industrial Team. If no agreement is reached after 6 months of negotiations, the Department of Energy may grant such a license itself if it determines that the invention owner has not negotiated in good faith. Any assignment of the invention must be made subject to this requirement.

The following discussion provides additional justification for the SECA pilot-program exceptional circumstance:

- By making the intellectual property available to the Industrial Teams on a non-exclusive basis, the value of an individual license may be less but the cumulative value may very well be greater. If the intellectual property is important, all Industry Teams will need to have it to remain competitive, the baseline of the technology will be raised.
- Making the intellectual property available to as many Industrial Teams as want it, would ensure that
 the individual technology pieces are incorporated into the best designs versus that of only the highest
 bidder (not necessarily the technology with the best chance for commercial deployment). This would
 benefit U.S. National interests.
- If Core Technology Program participants could exclusively license to anyone they chose, including
 outside of the SECA Industrial Teams, then it would be unlikely that Industrial Teams would be willing
 to collaboratively define the Core Technology Program objectives. Based on past fuel cell program
 experience, Industrial Teams in general would prefer to keep most development work in-house. This
 is not necessarily the best technical approach or best use of public funds since an individual company

would typically not possess a concentration of the best talent; redundant equipment and facilities would have to be purchased; and redundant research and development efforts would have to be performed. This would negate the SECA goal of leveraging the most difficult problems to accelerate commercialization of this nationally important technology.

A market for the intellectual property is being created. The Core Technology Program participants will have a ready set of potential licensees to which they can license their invention(s), and, if the Industrial Teams are successful in commercializing their fuel cell systems, reap income in the form of royalties or cash payment. Also, in many cases where difficult negotiations for exclusive arrangements can keep intellectual property unavailable for significant lengths of time, companies can find ways to bypass intellectual property held by others. There is less incentive for a company to circumvent another entity if a mechanism is in place to make the intellectual property readily and immediately available. Parallel negotiations for non-exclusive licenses and the time limits imposed by the Exceptional Circumstance should significantly shorten the time it takes to implement new intellectual property. In addition, once an agreement is reached with one Industrial Team, agreements with the other Teams should quickly follow if the intellectual property has general applicability.

Appendix A Breakout Session Results

I. Materials and Manufacturing – Session A Group Summary

Issues

In order to achieve the SECA goals, the following technology issues received the largest number of votes:

- Metallic interconnects
- Optimize fabrication technology
- New stack designs
- Better materials for seals that are low cost and easy to fabricate into the stack
- Reducing stack operating temperatures to below 700°C to allow use of bare metallic interconnects

R&D Opportunities

The R&D opportunities were categorized into three header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

Advanced Integrated Fabrication Technology

- Single-step SOFC fabrication technique
- Develop low-cost thin-film fabrication/ manufacturing techniques

Component Development

- Low temperature development ≤ 800°C
- Development and investigation of metal interconnect technology

New Stack Design

- New cheap stack design to minimize interconnects and seals
- New stack designs

Actions

The group's blend of industry, academia, government and national laboratory personnel produced several in-depth technical discussions from a theoretical point of view as well as a "real world perspective." These proved to be a very valuable exchange and dialogue for all the participants. Given the timing constraints, it was only possible to develop specific actions for the top three opportunities.

Low Temperature Component Development:

- Mechanistic studies of electrode kinetics.
- Optimize performance of mixed conducting cathodes
- Develop a direct oxidizing anode

- Oxidation resistant anode
- Modify anode to control ΔT due to internal reforming
- Investigation of commercially available alloys for metallic interconnects
- Cathode side surface treatments on commercially available metallic interconnect materials
- Investigation of developmental alloys for metallic interconnects

Investigate and Develop Metal Interconnect Technology:

- Interconnect designs that minimize material use
- Investigation of the interconnect and electrode interface
- Explore thermal spray technique
- Control and optimization of sintering of ceramic multi-layers

Advanced Fabrication Technologies:

- Manufacturing cost estimation studies
- Increase mechanical strength of electrode support (or SOFC stack)

In addition to identifying the engineering, development, and research actions, a table was prepared indicating a consensus on the amount of time required to resolve each identified action. In all cases but one, the amount of time required was in the three to six year timeframe. This agrees with the anticipated SECA schedule.

MATERIALS AND MANUFACTURING - SESSION A

PARTICIPANTS

Name	Affiliation		
Gerry Agnew	Rolls-Royce		
Bill Barker	ITN Energy Systems, Inc.		
Scott Barnett	Northwestern University		
David Bauer	Ford Motor Co.		
Donald Beal	Performance Ceramics Co.		
Ray Benn	United Technologies Research Center		
Brian Borglum	Siemens Westinghouse Power		
Larry Chick	PNNL		
Mike Cobb	Michael A. Cobb and Co.		
Tom George	DOE/NETL		
Diane Hooie	DOE/NETL		
Roddie Judkins	Oak Ridge National Laboratory		
Benson P. Lee	Technology Management, Inc.		
Ron Loehman	Sandia National Labs		
Bill Luecke	NIST - Ceramics Division		
John A. Olenick	Advanced Refractory Technologies, Inc.		
James Ralph	Argonne National Laboratory		
Robert J. Remick	IGT/GRI		
Bill Schweizer	McDermott/SOFC		
Mohinder Seehra	West Virginia University		
Scott Swartz	NexTech Materials		
Anil Virkar	University of Utah		
Steve Visco, Chairperson*	Lawrence Berkeley National Lab		
Conghua Wang	University of Pennsylvania		
FACILITATOR: Howard Lowitt	Energetics, Incorporated		

^{*} = Presenter for report-out

Materials and Manufacturing - Session A: Opportunities Database

- Design interconnects alloy that forms a conducting scale
- Improved BOP/system integration
- Integrate experiments and modeling to minimize sintering and expansion stresses in co-fired ceramic layers
- Aqueous processing and fabrication of SOFC materials (where feasible)
- Develop metallic interconnect supported design and fabrication process
- Identification of new, high performance, lower cost materials.
- Develop new multiplayer fabrication capabilities for cofiring
- Search/test new materials for seals

- Chromium-free metallic interconnect
- Cheap protective coatings for metallic interconnects
- Develop viable electrolyte with 10x higher 0⁻ conductivity than YSZ
- Develop lower temperature materials
- Develop lower cost thin film manufacturing (no UHV)
- New anodes/cells that can use hydrocarbon fuels
- New, highly electro-active electrodes and development of electrode-supported cells
- Development of single-step firing of cells
- Single step cell fabrication technology

- · Manufacturing cost models
- Design for manufacture
- Cell stack design
- Identify/quantify trade-offs between: pore size dist/amount, gas flow, SOFC performance, and mechanical properties
- Develop reliable seals and prove new designs
- New electrode materials
- Develop cell materials capable of high power density at 700°C and below
- Develop new stack designs to simplify manufacturing

- High temperature corrosion of metal interconnects and interfaces
- New stack designs
- Identify/develop alloys for interconnects
- Develop improved extrusion and molding technology for complex parts
- Identify and develop durable, hightemperature metal-based interconnects
- Custom formulation of metal interconnects
- New methods for high temperature, multi-material joining and sealing
- Identify and develop seal material/design systems

- Search/test alloys for interconnects
- Investigate novel stack designs
- Stack modeling
- Methods for low cost, high speed deposition of SOFC stack materials
- Develop new materials having increased ionic conductivity at reduced temperatures
- Develop manufacturing technology which makes stack production cost low

Materials and Manufacturing – Session A: Issues

(**k** = Vote for Priority Topic)

Given a good fuel cell? How does one verify — technical test issues k Rapid cooldown technique thermal designs Activation potential Sulfur poisoning of anode Complicated thin film/coating technology New stack designs kkkk Innovative stack design	Concurrent operation of metallic plates at operating temperature of ionic conducting ceramics Better materials for seals low cost, easy to fabricate into stack kkkk Durable sealing (stack design/bonding agent) kkk Development of thinner cell components to lower amount of material per cell Hydrogen as fuel, new anode Stack must survive rapid thermal cycling	 Interconnect inventory High working temperature 800°C → 700°C Bi-polar supported (metallic) SOFC for cost reduction Cathode performance Expensive cathode materials Synergistic impact of R&D on issues Greater, more available body of knowledge and data (knowledge transfer includes from other fields) Basic knowledge and data relating to interconnects Multiple materials currently require multiple fabrication steps/ processes, single step process needed Low-cost manufacturing of tri-layer cells Too many manufacturing steps k 	Metallic interconnects	Complicated manufacturing procedures requiring multiple firings of ceramics SOFC materials are not computer components Optimize fabrication technology KKKKKKKK Small scale (size) extrusion technology needed K Development of multimaterial co-firing to lower manufacturing costs Low cost, efficient materials Ability of SOFCs to follow load Single SECA goals (identify intermediate niches)	Lack of anodes capable of high fuel conversion with minimal prereforming (maximized efficiency) Req. use of high cost, dissimilar material properties materials that cause integration challenges Long term chemical compatibility data
---	--	---	------------------------	---	---

Materials and Manufacturing – Session A: R&D Opportunities

(**k** = Vote for Priority Topic)

ADVANCED INTEGRATED FABRICATION TECHNOLOGY	COMPONENT DEVELOPMENT	New Stack Design
Single step SOFC fabrication technique kkkkkk Develop low-cost thin-film fabrication / manufacturing techniques kkk Integrated cell/stack design with fabrication process development	Low temperature development <800 kkkkkkk Identify new, novel seals and separators for test and evaluation k Development and investigation of metal interconnect technology kkkkkkkk	 New stack design(s)

Materials and Manufacturing – Session A: What Are the Actions Needed to Take Advantage of the Opportunities?

R&D OPPORTUNITY	Actions	Type of	0-3	3-6	6-10	Industry	ACADEMIA	NATIONAL
		ACTION						LABS
LOW TEMPERATURE COMPONENT	Mechanistic studies of electrode kinetics	R	X				A	
DEVELOPMENT	Optimize performance of mixed- conducting cathodes	D	X			I		N
	Develop direct oxidizing anode	R	X	X			A	
	Oxidation resistant anode	R	X	X			A	N
	Modify anode to control ΔT due to internal reforming	D/E	X	X		I		N
	Investigation of commercially available alloys	D	X				A	
	Cathode side surface treatment on commercially available alloys	D	X	X		I		N
	Investigation of developmental alloys	D	X	X		I	A	N
INVESTIGATE AND DEVELOP METAL	Interconnects designs that minimize material use	Е	X	X				N
INTERCONNECT TECHNOLOGY	Investigation of interconnect, electrode interface	R	X	X			A	N
	Explore thermal spray techniques	D	X	X				N
	Control and optimization of sintering of ceramic multi-layers	R/D	X	X		I		N
ADVANCED FABRICATION TECHNOLOGIES	Manufacturing cost estimation studies	D/E	X	X		I		N
	Increase mech. strength of electrode support (or SOFC stack)	D/E	X	X	X	I		N

Key: E = Engineering D = DevelopmentR = Research

Materials and Manufacturing – Session A: Report-Out

TECHNICAL ISSUES	R&D OPPORTUNITIES	KEY OPPORTUNITIES	ACTIONS
Metallic interconnects Optimize fabrication technology Lower temperature materials Durable seals New stack designs (current stack designs)	Component development ! Low temperature electrode development ! Develop and investigate metal interconnect technology New stack design ! Minimize interconnects and seals ! Trade-offs driving design of stacks Advanced integration fabrication technologies ! Single-step fabrication technique ! Low-cost thin-film techniques	Low Temperature Component Development	Mechanistic studies of electrode kinetics Optimize performance of mixed-conducting cathodes Develop direct oxidizing anode Oxidation resistant anode Modify anode to control ΔT due to internal reforming Investigation of commercially available alloys Cathode side surface treatment on commercially available alloys Investigation of developmental alloys
		Metal Interconnect Technology Advanced Fabrication Technologies	Interconnects designs that minimize material use Investigation of interconnect, electrode interface Explore thermal spray techniques Control and optimization of sintering of ceramic multi-layers Manufacturing cost estimation studies Increase mech. strength of electrode support (or SOFC stack)

II. MATERIALS AND MANUFACTURING - SESSION B GROUP SUMMARY

Issues

In order to achieve the SECA goals, the following technology issues received the largest number of votes:

- Fabrication of stacks from cells
- Thin-film manufacturing cost
- Interconnects metal or oxide

While the costs of raw materials is not a major concern now, availability of certain materials (e.g., LSM and YSZ) could be problem down the road if the market takes off.

R&D Opportunities

The R&D opportunities were categorized into five header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

Design

• Develop novel, low-cost cell stack design concepts

Interconnects

 Develop new interconnect alloys from fundamental understanding of oxidation kinetics and oxide conductivity

Fabrication/Manufacturing

- Cost-effective fabrication of high-performance cell stacks including tri-layers, thin electrolyte, electrolyte coating, low temperature, and colloidal deposition
- NDE to enhance manufacturability

Materials Properties

- Develop internally reforming stacks (anode or manifold)
- Develop different anode material for different fuels

Interface

- Fundamental investigations into interfaces-microstructures and catalytic properties
- Investigate novel interlayer for adhesion and chemical protection

<u>Actions</u>

Key action steps were developed for the top three opportunities.

Develop cost-effective fabrication techniques for high performance fuel cell stacks:

- Conduct fundamental studies into why defects occur
- Investigate large scale thin film deposition
- Develop in-situ NDE methods for identifying defects
- Adapt existing ceramic technique for specific fuel cell designs
- Develop low cost interconnect and seals

Develop new interconnect alloys from fundamental understanding of oxidation kinetics and oxide conductivity:

- Examine interface and coatings inter-relations and stability
- Examine stability and electric transport at interface
- Conduct surface modification studies

Develop compact, reliable, low cost fuel cell design concepts:

- Immediately study design as function of performance parameters
- Define cost and performance specifications
- Create ability to evaluate thermal and chemical properties with in-situ diagnostic tools
- Determine effects of high power density on long-term performance
- Build in design review to ensure flexibility to respond to change
- Evaluate transport phenomena
- Evaluate feasibility of internal reforming under multi-fuel conditions

MATERIALS AND MANUFACTURING - SESSION B

PARTICIPANTS

NAME	AFFILIATION
Harlan Anderson	University of Missouri at Rolla
Tim Armstrong	Oak Ridge National Lab
Glen Benson	Aker Industries
Sandy Dapkunas	NIST
Bill Dawson	NexTech Materials
Lutgard C. DeJonghe*	UCB/LBNL
Richard Dye	DOE
Peter Faguy	MicroCoating Technologies
Robert Glass	LLNL
Jack (John) Hirschenhofer	Parsons
Kevin Huang	University of Texas at Austin
Kevin Krist	GRI
Meilin Liu	Georgia Tech
Scott Mao	University of Pittsburgh
James Marsh	Concurrent Technologies Corporation
Gary G. McVay	PNNL
Nguyen Minh	Honeywell
Udaya Rao	NETL
Carl Reiser	International Fuel Cells
Richard Rozance	Car Sound Exhaust Systems, Inc.
Chin Schilling	Iowa State University
Dinesh K. Shetty	Materials and Systems Research, Inc.
Subhash C. Singhal	PNNL
Jeff Stevenson, Chairperson	PNNL
Michael Thompson	PNNL
Wayne L. Worrell	University of Pennsylvania
FACILITATOR: Rich Scheer	Energetics, Incorporated

^{*} = Presenter for report-out

Materials and Manufacturing – Session B: Scientific and Technology Issues

 $(\mathbf{k} = \text{Vote for Priority Topic})$

MANUFACTURABILITY	INTERCONNECT MATERIALS	COST OF RAW MATERIALS	PERFORMANCE	STACK SYSTEM DESIGN AND INTEGRATION
For target power density no high volume, low-cost tri-layer fabrication technology exists kkkkk Need for system integration of stack components and automated manufacturing Lack of alternatives to the costly EVD process for depositing the electrolyte k Basic understanding of how electrode/electrolyte reliability is affected by colloidal deposition parameters k Fabrication of stacks from cells kkkkkkkkk Thin-film manufacturing cost kkkkkkk Lack of NDE for manufacturing	Lifetime of interconnect materials Interconnect metal or oxide? kkkkkk Lack of inexpensive thermally reliable seals Metal interconnects needed above 650°C	Low demand for LSM, YSE materials Availability of high V, low-cost raw material k	O of 60 to 70% will require 0.85 V/C+; close to theoretical present is 0.7 V/C Slow electrode kinetics at low temperature Limited temperature range Catalysis limiting issues below 700°C Lack of NDE techniques to predict remaining life kk Specific power (W/cm²) k Anode composition and structure to permit full in situ reforming k Hydrocarbon tolerances and poisoning k Design of novel interfaces with minimum resistance k	Thermal management Low cost PEN with controlled morphology electrodes k Need for inexpensive thermal insulation Fuel delivery to all cells in stack Serviceability of complex fuel stack Materials compatibility Settling too soon on tech design Gas manifolding on mass customization of core module Need to recycle address disposal/recycling of materials from stack Thermal cycling of scaled-up reduced temperature planar stacks

Materials and Manufacturing - Session B: R&D Opportunities

(**k** = Vote for Priority Topic)

DESIGN	Interconnects	FABRICATION/	MATERIALS PROPERTIES	Interface
Improve thermal cycle Develop measures to shorten start-up K Develop novel, low-cost cell stack design concepts Kkkkkk Compact with improved reliability Minimize/eliminate sealing issues	Compliant metallic interconnect	MANUFACTURING Cost-effective fabrication of high-performance cell stacks Trilayers Low-cost thin electrolyte processing technology Develop and scale up electrolyte coating process and thin film stack manufacturing Low temperature Study colloidal deposition parameters impact on reliability flaw development during coating/debinding/firing kkkkkkkkk Develop a repetitive manufacturing process Flaw development in co-firing (suppression) NDE to enhance manufacturability kk Develop process models for fabrication k	Lower operating temperatures Solve film adhesion problems Develop different anode material for different fuels	Transport across heterogeneous interfaces and electrode architecture performance Fundamental investigations into interfaces-microstructure and catalytic properties kkkk Investigate novel interlayer for adhesion, chemical protection kkkk

Materials and Manufacturing - Session B: Actions

R&D OPPORTUNITY	BRIEF DESCRIPTION	Type of Action	KEY ACTION STEPS	LEAD ROLES	OTHER POINTS
	OF OPPORTUNITY				
Develop cost-effective fabrication techniques for high performance fuel cell stacks	Multi-cell stack extrusion Long term-new ways to make ceramics Lack of volume is main reason costs of manufacturer is high Dramatic cost reductions are needed. Capital costs of equipment are high In situ firing? Core can participate in long term — trilayers and PENs One-step firing Defects are a problem for reliability Start with simple traditional techniques	R First 3 years use today's process Longer term other methods will be needed	Fundamental studies into why defects occur Investigate large scale thin film deposition – review existing work Develop in-situ NDE methods for identifying defects Adapt existing ceramic technique for specific fuel cell designs Develop low cost interconnect and seals	Industry Longer-term concepts – consortia –NL, U	Do not use material at temperatures higher than you make it
Develop new interconnect alloys from fundamental understanding of oxidation kinetics and oxide conductivity	Very difficult problem! Chromium-are there other materials? Compounds Oxides, etc. as coatings? Need scale that is good conductor Lowering temperature can help Coatings are possibility but have own problems	Mostly R and some D	Ongoing throughout program Examine interface and coatings inter-relations and stability Examine stability and electric transport at interface Conduct surface modification studies	National labs and universities Consortium with industrial input	Watch over next 3-5 years
Develop compact, reliable low cost fuel cell stack design concepts	Design new stacks "core" Making stacks small involves core design issues Thermal and mass flow in compact SOFC Modify existing stacks "Industry Group" Choice of fuel is key	Core D and R Industry E	Study design as function of performance parameters 1st year Define cost and performance specifications Create ability to evaluate thermal and chemical properties in situ diagnostic tools	Industry lead in design	Need to have ability to change and avoid "lacking in" to particular designs Focus as quickly as possible on limited number of designs

Materials and Manufacturing - Session B: Actions (Continued)

R&D OPPORTUNITY	Brief description of Opportunity	Type of Action	KEY ACTION STEPS	LEAD ROLES	OTHER POINTS
Develop compact, reliable low-cost fuel cell stack design concepts (con't)	•	•	Determine effects of high power density on long term performance Build in design review to ensure flexibility to respond to change Evaluate transport phenomena overtransient long term condition Evaluate feasibility of internal reforming under multi-fuel conditions	•	•

Key: E = Engineering

D = Development

R = Research

Materials and Manufacturing – Session B: Report Out

DESIGN AND MANUFACTURING	Breakout Session Overview	Materials	CLOSING REMARKS
Design is developed by industry Design affects manufacturability Novel ideas should be explored Address transient operations/thermal cycling Near-term – refining tapecasting Long-term – "multi-cell extrusion"	Achieving cost goals is dominating factor Major materials issues More specific than manufacturing issues at this time	Nature of electrolyte and electrode did not emerge as major issue Low temperatures, different story (e.g., power densities) T(E); A/cm ² Interconnects are a major area to address Membrane contacts Oxidation	 Difficult balance – design do not "lock in" too soon but focus as soon as possible ! Design reviews • Mobile ↔ stationary fuels

III. FUEL PROCESSING - SESSION A GROUP SUMMARY

Issues

In order to achieve the SECA goals, the following technology issues received the largest number of votes:

- Catalysis reduction of the size of processing hardware for multi-fuel
- Operation with little or no water
- Gas contaminant removal or purification
- Very rapid transient response
- Reformer stability during transients
- Fully integrated fuel processor
- Ability to internally reform natural gas

Overall, what is needed is a fully integrated fuel processor with multi-fuel capability that is small and is sulfur tolerant. Also, the reformer must have operational stability during transients, start-up, and shut-down conditions. The critical challenge mentioned repeatedly is either sulfur cleanup or sulfur tolerance. Without resolving this issue, many candidate fuels and markets cannot be considered for solid-state fuel cell system applications.

R&D Opportunities

The R&D opportunities were categorized into five header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

System Development and Demonstration

- System level reformer development
- Development of low-cost, accurate sensors
- Multi-path approach to demonstrate electrochemical reformer

Fuel Characterization

None

Clean-Up Process

- Develop a liquid phase de-sulfurization system
- Sulfur removal gas phase H₂S, organic sulfides

Catalyst Development

- Reformer catalyst development
- Catalyst characterization performance, life, cost
- Combinatorial approaches to catalysts

Modeling

- System modeling to identify optimal strategies for integrating stack and reformer designs
- Transient control, dynamic temperature, and reaction rates in reformer catalysts

Actions

System Level Reformer Development:

- Develop commercial, integrated, reliable reformer
- Develop modular packages for a family of sizes and functions or parameters

Fuel Processor Catalyst Development:

- Determine and characterize catalyst durability vs. fuel and operating conditions
- Improve catalyst yield and efficiency
- Characterize catalysts for sulfur tolerance and fuel consumption
- Develop alternate catalysts via combinatorial approach
- Evaluate sulfur removal techniques in liquid and gas phase
- Define level of sulfur cleanup requirements by fuel
- Evaluate and investigate reaction chemistry
- Evaluate and demonstrate small integrated efficiency reformer
- Maintain data in catalyst database/reformer handbook
- Test method and standard procedures to benchmark designs vs. target requirements
- Evaluate close coupled in-stack reforming
- Evaluate POX and ATR conversion selectivity
- Optimize reformer
- Evaluate integrated system in a remote field location
- Demonstrate catalyst endurance characteristics

System Modeling to Integrate Stack and Reformer Designs:

- Evaluate close-coupled in-stack reforming
- Develop user friendly commercially supported modeling package for reaction kinetics through coupled reformer and stack

The group identified research, development, and engineering actions that would need to be completed within the next 0-5 years and within 5-10 years to achieve the SECA vision. Within the next 5 years much catalyst development and system development activities need to begin. Initially, databases on catalysts and reformers need to be complied and made available based on characterization and trade-off studies and evaluations. From 5-10 years, system optimization and demonstrations should be stressed.

FUEL PROCESSING - SESSION A

PARTICIPANTS

NAME	AFFILIATION
Dave Berry, Chairperson	DOE/NETL
Rich Carlin	Office of Naval Research
Ravi Chandran	MTCI
Herb Dobbs	U.S. Army TACOM
Chris Egan	U.S. Navy/NAVSEA
Lyman J. Frost*	INEEL
M. James Grieve	Delphi Automotive Systems
Douglas Gyorke	DOE/NETL
Brian James	Directed Technologies, Inc.
Jason Lewis	DOE/NETL
Joe Pierre	Siemens Westinghouse
R. Srinivasan	The Johns Hopkins University
Thomas I. Valdez	Jet Propulsion Laboratory
Jud Virden	PNNL
Dennis Witmer	University of Alaska Fairbanks
Joe Woerner	Analysis and Technology
Richard Woods	Hydrogen Burner Technology
John Yamanis	Honeywell, Morristown, NJ
FACILITATOR: Joe Badin	Energetics, Incorporated

^{* =} Presenter for report-out

Fuel Processing – Session A What Are the Science and Technical Issues to Achieving Vision?

CATALYST ISSUES	FUEL ISSUES	GAS CLEAN-UP	OPERATIONAL ISSUES	Cost Issues	System Integration
Catalyst availability for variety of fuels k Lack of more predictive catalyst design tools Catalysis - Reduction of size of processing hardware for multi-fuel kkkk Catalyst life Coking problems kk Electrochemical reformers k Sulfur-tolerance and direct electrochemical oxidation kk ! Stable catalyst (sulfur) ! Rapid start-up ! Partial Ox. Reformer Sulfur removal, sulfur tolerance to reformer catalyst k	Operation with little or no water (gasoline, diesel) kkkkk Small and efficient P.O. reformer for gasoline and diesel 90% conversion k Direct diesel (multi-fuel) SOFC, Eliminate reformer k Partial oxidation of liquid fuels with oxygen k Feedstock flexible k Logistic fuels – compact, fuel-flexible, rapid response	Active sulfur removal gas phase k Desulfurization technology – needs to be high capacity, without need for hydrogen, compatible with metcaptions and thiophenes Gas contaminant removal (or) purification kkk Pure hydrogen stream Selective gas separation technologies: oxygen, hydrogen, CO, etc. k	Load following fuel source k 20 to 1 turndown sensors Requirement for very rapid transient response rapid transient resp. kkk Reformer stability during transients (startup-shut down – ramp) kkkk Control sensor how do we know when the reformer is deteriorating? Freeze protection Cycling	Low-cost high temperature heat exchangers K Materials of construction (high-temperature) Hydrogen embrittlement Catalyst cost O&M	Fully integrated fuel processor T, heat balance kkkk Size reduction issues – heat management issues Start-up requirements cold-hot kk Achieving 60-70% efficiency goal without bottom cycle and in volume/wt envelope is challenging Ability to internally reform (in stack) I Natural gas kkk Control system k

Fuel Processing – Session A What Are the R&D Opportunities to Overcome the Issues?

 $(\mathbf{k} = \text{Vote for Priority Topic})$

SYSTEM DEVELOPMENT AND	FUEL CHARACTERIZATION	CLEAN-UP PROCESSES	CATALYST DEVELOPMENT	Modeling
DEMONSTRATION Develop low cost high temperature heat exchangers k DoE work in high "R" insulations k Development of low-cost, accurate sensors kk Modular control system concepts System-level reformer development kkkkkkkk Microchannel reformers for reduced size and integration Multi-path approach to demonstrate electro-chemical reformer kk Develop low-cost, fully integrated fuel processor module k Operational characterization of "state-of-the-art" fuel processors (Team)	Define and characterize fuels Decide what fuel is best – reference fuels	Sulfur removal − gas phase H₂S, organic sulfides kk Long life regenerable sulfur sorbents − demonstrate Nanoporous ceramic membranes for gas purification Develop a liquid phase De-S system kkk Mixed oxide conductors for fuel processing	Catalyst characterization – performance, life, cost kk Develop multi-fuel single catalyst Reformer catalyst development kkkkkkk Steam reforming POX reforming K ATR K Regenerable catalyst, also with insitu gas cleanup Low temperature (400-600°C) catalysts for direct oxidation k Combinational approaches to catalysts kk Nanostructural catalysts Catalyst R&D Sulfur tolerant Long life Low cost Size reduction	Develop reaction kinetics modeling Different fuels Different water Coke formation System modeling to identify optimal strategies for integrating stack and reformer designs kkkk Modeling heat flows Chemical reaction modeling for POX k Fundamentals of hydrocarbon reforming (in-situ,) k Transient control dynamic temperature, temperature and reaction rates in reformer catalysts (chemical modeling) kkk System modeling "optimizations" toward mass customization

Fuel Processing – Session A What Are the Actions to Take Advantage of the R&D Opportunities?

System-Level	SYSTEM MODELING TO	FUEL PROCESSOR CATALYST DEVELOPMENT	LEAD ROLE(S)
REFORMER	INTEGRATE STACK AND		
DEVELOPMENT	REFORMER DESIGNS		
Develop a commercial, integrated, reliable reformer Modularity – packages/family of sizes and functions (parameters)	Evaluate close coupled instack reforming Develop user friendly modeling package for reaction kinetics through coupled reformer and stack Commercially supported platform Demonstrate and validate	 Determine, characterize catalyst durability vs. fuel and operating conditions Database (0-5 years) Improve catalyst yield/efficiency life (Research) Characterize catalysts for: ! S tolerance ! Steam/C ratio (min) ! Fuel composition Develop alternate catalysts (combinatorial approach) ! Lower cot ! Non-noble metal ! 0-5 years: membranes? Benefits/tradeoffs ! Sulfur tolerance removal Evaluate S removal techniques in liquid and gas phase ! Disposable ! Regenerable ! Active Define level of S clean-up requirements (by fuel Evaluate; investigate reaction chemistry (Research, Development) ! Liquid fuels ! Steam ! Pox ! ATR ! Electro-chem Evaluate and demonstrate small integrated efficiency reformer (Engineering, Development) (Gaseous) ! Gaseous fuels ! Steam ! Pox ! ATR O-5 Years – Maintain data of catalyst database/reformer handbook Test method and standard procedures to benchmark designs vs. target requirements Evaluate close coupled in-stack reforming 0-5 years - Evaluate determine P.Osooting, ATR conversion selectivity (temp range) diesel and gasoline JPx Trade-offs of reformer types by application (Engineering) 5-10 Years - Evaluate integrated system in remote field location Evaluate and demonstrate a small, integrated, eff. reformer (Engineering) 5-10 Years - Demonstrate catalysts endurance characteristics 	Ultimately – industry Core tech – university and national labs

Fuel Processing - Session A: Report-Out

SCIENCE AND TECHNICAL ISSUES	R&D OPPORTUNITIES	ACTIONS
 Cost Issues Integration Fully integrated fuel processor Operational Reformer stability during transients (startup, shutdown, etc.) Gas Cleanup Gas contaminant cleanup (include S) Fuel Issues Min S/C ratios Catalyst Issues Develop for multi-fuel and size ↓ S-tolerance 	Modeling Reaction kinetics Systems modeling Catalyst Development New catalysts and characterization of current S-tolerance Clean-Up Processes S-removal!! Other contaminants System Development Reformer integration with other components Fuel characterization	 System Level Reformer Development ! Split – gaseous liquid ! Further – steam, Pox, ATR, Electrochemical (liq) Fuel Processor Catalyst Development Systems Modeling System (0-5 years) ! Evaluate, investigate reaction chemistry ! Characterize small reformers ! Database on catalysts and reformers ! Standard procedures for test/targets ! Trade-offs by reformer type and application – list all parameters (soot conversion, others) System (5-10 years) ! Optimize ! Demonstrate Catalyst Development (0-5 years) ! Improve catalyst conv. efficiency and life ! Characterize existing catalysts (S, S/C, etc.) ! Develop alternate catalysts (cost↓, S) ! S cleanup, liq phase ! Membranes Catalyst Development (5-10 years) ! Demonstrate! Systems Modeling ! Evaluate coupled reformer/stack ! Develop user friendly commercially supported modeling for reaction kinetics → coupled reformer/stack

IV. FUEL PROCESSING - SESSION B GROUP SUMMARY

Issues

In order to achieve the SECA goals, the following technology issues received the largest number of votes:

- Availability of low-cost, small-scale reformers to deal with diesel and logistic fuels
- Deactivation of catalyst
- Internal reforming thermal management and poisoning
- Performance with respect to durability, life, and load following.

R&D Opportunities & Actions

The R&D opportunities were categorized into five header topics. However, the group did not vote on specific opportunities, but instead they voted on the header topics. Therefore, the following are the three header topics that received the most votes with only the first three bullet details presented.

Making Diesel Fuel Processor Work

- Make poison resistant partial oxidation reactor
- Demonstrate a two-stage diesel steam reformer
- Develop liquid fuel processors to remove sulfur

Propane/Natural Gas Fuel Processor as Cheap as Possible

- Develop low-cost, high-efficiency gaseous fuel reformer
- Develop a very inexpensive oxidative reforming unit
- Design for low cost manufacturing

Internal Reforming

- Design and build models for internal reforming stack
- Develop graded anode
- Develop oxidative internal reforming process for natural gas and propane

Actions

The group developed actions from the top three categories of R&D opportunities.

Develop a Compact Fuel Processor for Diesel and Logistics Fuels:

 Novel fuel conversion processes, e.g., advanced oxygen sources for partial oxidation and microchannels to enhance heat transfer

- Fuel pre-processing systems to remove troublesome impurities before they are charged to the fuel processor
- Anode catalysts that are resistant to sulfur and carbon
- Advanced balance of plant systems

These activities were categorized as spanning research and development.

Make Light Fuels Processors (Natural Gas, Propane, and Gasoline) as Low Cost and Compact as Possible:

- Thermal integration
- Miniaturization of equipment for 5 kW
- Start by simplifying fuel processors designed for PEM
- Multi-fuel R&D
- Integrated fabrication development
- Lowering components costs through DFMA and other means

These activities were categorized as primarily engineering.

Develop Internal (On-Anode) Reforming Technology:

- Steam reforming and POX
- Lab tests of internal reforming systems and use the data acquired to develop electrochemical and thermodynamic models of processes and obtain fundamental knowledge of them
- Multi-fuel tolerant core module
- Graded anode technology
- Advanced fuel-mixing concepts to facilitate heat transfer and management

Internal reforming was described as the "holy grail" of fuel processing, and activities supporting it are staunchly in the research end of the action spectrum.

FUEL PROCESSING - SESSION B

PARTICIPANTS

NAME	AFFILIATION
Buddy Hartberger	U.S. Coast Guard
Zohair Ismail	U.S. Army CEOM
Craig Linne	Visteon Automotive
M. Mundschau	Eltron Research
M. Mansour	ThermoChem
Kirby Meacham	Michael A. Cobbs & Co.
Larry Osgood	Consulting Solutions/Propane Council
Prabhakar Singh	Pacific Northwest National Laboratory
Jack Solomon*	Praxair Inc.
Walter Taschek	U.S. Army CECOM
W.P. Teagan, Chairman	Arthur D. Little
FACILITATORS: Phil DiPietro	Energetics, Incorporated
Robyn McGuckin	

^{*} Presenter for report-out

Fuel Processing- Session B: Issues

PERFORMANCE	STACK SENSITIVITY (SULFUR & SALT) POISON	LOW CAPACITY OF SYSTEM	INTERNAL REFORMING	FUEL EFFECT ON FUEL PROCESSOR	FUEL PROCESSING BOP
Long-term testing durability k Long life of reformer materials at low cost k Start-up time Load following k	Anode Poisoning Salt Sulfur	Difficult for Diesel k Availability of low cost small scale reformer kkkk Thermal losses in small systems Reliability at small scale	Poisoning K Cracking Thermal management KK Preconditioning of fuel	Deactivation of catalyst kkk Thermal Coking Sooting Poisoning	Sulfur aborption/disposal (filter cartridge) using alkali metal Long life desulfurizer k Water sufficiency

Fuel Processing – Session B: Opportunities

Making Diesel Fuel Processor Work kkkkkkkkk	PROPANE/NATURAL GAS FUEL PROCESSOR AS CHEAP AS POSSIBLE KKKKKKKKK	Internal Reforming kkkkkk	BALANCE OF PLANT kkk	OTHER ITEMS
Make poison resistant partial oxidation reactor ceramic membrane Demonstrate a two stage (diesel) steam reformer (fluid-bed/Plug Flow) for 100 kWe system and work backwards down Liquid fuel processors to remove sulfur—disposable filter-1 gallon can processes 20 gallons of fuel Come up with a dual catalyst that tolerate sulfur anode and coking Integrated reformer/heat transfer approach Microchannel Plate reformers Fuel preprocessor Remove sulfur Increase fuel quality Develop inert, stable materials	Develop low-cost, high efficiency gaseous fuel reformer Very inexpensive oxidative reforming unit for natural gas and propane Design for low cost manufacturing Integrated fabricate development	Models for internal reforming stack design – build Graded anode development Oxidative internal reforming process for natural gas and propane Mixing fuel in cell rather than plug flow to improve internal reforming Develop a multi-fuel tolerant internal reforming core module (cell)	Sensors Materials Manufacturing Techniques Reduce parasitic load	Accelerated durability testing reformer/stack Long term materials research and tests System optimization Ultra-rich internal combustion engine as POX fuel processor shaft power out quick start Coking-resistant coating for preconditioner

Fuel Processing - Session B: Actions

FUEL PROCESSOR FOR DIESEL AND LOGISTIC FUELS	ULTRA LOW-COST HIGH EFFICIENCY FUEL PROCESSOR FOR NATURAL GAS AND PROPANE	INTERNAL REFORMING (ON-ANODE)
Novel Processes Ceramic Membrane POX Integrated heat transfer microchannel /plate reformer Two stage heavy fuel steam reformer Materials resistant to impurities Pilot plant At 20 kW Fuel Pre-processing Liquid phase desulfurization Better ways to remove sulfur during processing Materials research to develop anode catalyst to resist sulfur and carbon BOP Systems integration Perform R&D on components with integration in mind Thermally integrated reforming	Develop low cost, high efficiency gaseous fuel reforming Steam POX Other Thermally integrated reforming Build at 5 kW Starting point. Simplify fuel processors designed for PEM stacks Multi-fuel R&D Integrated fabrication development Design low cost manufacturing	Most effort is on steam reforming, could look at POX as well Lab scale experimentation Modeling Thermal Chemical Electro-chemical Multi-fuel tolerant core module Graded anode Fuel mixing

Fuel Processing – Session B: Report-Out

Issues	Opportunities	ACTIONS	COMMENT
 Dealing with diesel and logistic fuels Lack of demonstrated internal reforming capability Low capacity Sensitivity of stack to sulfur, soot and salt Lack of demonstrated performance durability Reliability, long life, start up, multiple fuels, Diesel and logistic fuels makes problem much more difficult Internal reforming not clear you can be successful Low capacity Sulfur, soot, salt Performance 3 	Developing a compact (5-20 kW) diesel fuel processor	Diesel and logistic fuel Novel processing Fuel pre-processing Anode to resist sulfur and carbon BOP Natural gas, propane and gasoline Thermal integration Small size DFMA Internal reforming Lab tests/modeling Graded anode Fuel mixing	 Requirement of heavy fuels complicates vision Other goals at risk Alternate strategy – focus on natural gas for market introduction Early stage R&D on heavy fuels

V. Modeling and Simulation Group Summary

Modeling and simulation issues for fuel cells are best discussed by considering issues that impact the fundamental cell, component, stack, or system, or crosscut through all of these scales.

Issues

The following issues received the most votes:

- Validation/benchmark data for models/modeling
- Barrier posing of critical questions answerable by appropriate models
- Electro-chemical reaction rates and mechanisms
- Lack of suitable multi-physics engineering models
- Diversity of scales hinders Computational Fluid Dynamic (CFD) applications in multi dimensions at stack level.
- Total life cycle cost/performance analysis and optimization

R&D Opportunities

The R&D opportunities were categorized into five header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

Crosscutting

- Joint validation benchmarks where more than one group develops, characterizes, tests, and models
- Model SOFC operations: start-up, part-load, shut-down (load following)
- Define precisely what validation data are needed and get it
- Perform uncertainty analysis on fuel cell models at all levels (focus on numerical errors)

Cell/Fundamental

- Development of fundamental multi-dimensional models with emphasis on electrochemical and kinetic transport aspects
- Determine electro-chemical rates and mechanisms: measure and model
- Develop 3D fundamental multi-scale model for micro-structural analysis and design

Component

None

Stack

 Develop coupled multi-dimensional multi-physics engineering model for stack with benchmark problem set

System

• Build reliability model of SOFC system

Actions

To take advantage of the top three R&D opportunities, the following actions should be carried out:

Develop Models for the Cell and for the Stack:

- Multi-dimensional, multi-physics
- Develop benchmark problem set (for stack)
- Electrochemical, kinetic, transport emphasis for cell

Benchmark Development:

- Developed and characterize benchmark cells
- Test to provide data on benchmark cells
- Models will be developed for benchmark cells

Model SOFC Operation (Start Up, Part Load, Shut Down):

- Industries establish the off-design conditions and requirements
- Develop coupled transient models
- Validate the models

MODELING AND SIMULATION

PARTICIPANTS

NAME	AFFILIATION
Said Al-Hallaj*	IIT, Chicago
David H. Archer	Carnegie Mellon University
Mike Batham	California Energy Commission
David Black	CFD Research Corp.
Damon Bresenham	Generac Power Systems
Ismail Celik	West Virginia University
C.P. Chen	University of Alabama in Huntville
John Deur	ADAPCO
Emile Ettedgui	RAND
Randall Gemmen, Chairperson	DOE/NETL
Comas Haynes	Georgia Tech
Moe Khaleel, Chairperson	Pacific Northwest National Lab.
Jim Miller	Argonne National Lab.
Jeff Neff	EG&G
John Plunkett	EG&G
Michael Prinkey	Fluent Inc.
William Rogers	Fluent Inc.
FACILITATOR: Ed Skolnik	Energetics, Incorporated

^{*} = Presenter for report-out

Modeling and Simulation: What Are the Science and Technical Issues to Achieving the Vision?

CROSSCUTTING ISSUES	CELL/FUNDAMENTAL MODELS	COMPONENT MODELS	STACK MODELS	SYSTEM MODELS
Validation/benchmark data for models/modeling kkkkkkkk Barrier—posing of critical questions answerable by appropriate models kkkk Cost functions (accurate) {lack thereof} kk Dynamic communication with materials and manufacturing groups (lack thereof) kk Lack of education and training on fuel cell technologies k Connection and communication between modeling (scales of modeling) groups k Lack of public domain software k Need real-life values for model parameters k Lack of operating codes and standards for design modeling Lack of benchmark for verification	Electro-chemical reaction rates and mechanisms	Better models for fuel processing kk	Lack of suitable multi-physics engineering models Thermal, electro-chemical, transport coupling kkkkkk Diversity of scales hinders computational fluid dynamic (CFD) applications in multi-dimensions at stack level kkk Lack of a public domain research code for multi-dimensional modeling at the stack level k Methods for determining fabrication stress k Simulating indirect internal reforming transport phenomena Interface properties for PEN material and seals Reliability model Need for handbook approach for stack	Total life cycle cost/performance analysis and optimization Model cost/ maintenance trade-offs Fuel cell fabric. Auxiliary equipment installation Kkk Reliability/ Availability/ Maintainability (RAM) models

Modeling and Simulation: What Are the R&D Opportunities to Overcome the Issues?

	Crosscutting	CELL /FUNDAMENTAL	COMPONENT	STACK	System
Validation Oportunities	Define precisely what validation data that we need and get it (database) kkkk	Material databases electrochemical and thermal and failure data Develop tests and test standards for measuring material properties especially interfacial properties			
Computation Opportunities (Modeling)	Model SOFC Operations: Start-up, part-load, shut-down (Load following) kkkkk Handbook of Fuel Cell Model equations and thermal papers k Thermoeconomic design studies k Develop efficient numerics for such complex problems k Perform uncertainty analysis on fuel cell models at all levels (focus on numerical errors) kk	Development of fundamental multi-dimensional models which emphasizes on: electrochemical, kinetic transport aspects on the cell level. kkkkk Develop 3D fundamental multi-scale model for microstructural analysis and design kk	Fuel reformation models k	Develop coupled multidimensional multi-physics engineering model for stack with benchmark problem set	Build reliability model of SOFC system kk Build diagnostic model of SOFC system Fuel cell cost algorithms k
Joint Validation/ Computation Opportunities	Benchmarks more than one group develop and characterize same cell design more than one group test above and provide detailed data more than four groups model kkkkkk Define metrics or figure of merit and how they relate to one another k	Determine electro-chemical rates and mechanisms: measure and model kkk Model Equation Development Research on kinetics (electrochem and reforming) Propose and test models Publish all results		Understand failure mechanisms in stack/cell k	

Modeling and Simulation: What Are the Actions to Take Advantage of the R&D Opportunities?

R&D OPPORTUNITY	ACTIONS 0-5 YEARS	ACTIONS 5-10 YEARS	LEAD ROLE	OTHER ISSUES
DEVELOP MODELS FOR STACK AND CELL • Multi-dimensional, multi-physics • With benchmark problem set (for	Evaluate (and communicate) existing model base (E)		Government, Industry (NETL) with Industry and Academia	Consider concurrent engineering Support Vision 21 virtual plant demonstration prototyping
stack) • Electrochemical, kinetic, transport emphasis for cell	 Different groups to do different models electrochemical, kinetic, etc. (R) Develop design/applications models that address SECA vision (D) Incorporate into overall system model (E) 	Refine models as necessary (input from benchmarks) (D) Accommodate technical breakthroughs Modeling to accommodate markets (implement models P/E we have developed) (D/E) Reduce the turn-around time to speed the design cycle (D)	Government initiates, develops consortium of government, industry, academia; academia or national lab appointed to coordinate	
BENCHMARK DEVELOPMENT • >1 Group development and	 Develop and characterize benchmark cells (D/E) 		Government with academia	none
characterize same cell design 1 Group test cell and provide	Test and provide detailed data (D/E)		Government with academia	
detailed data • >4 Groups model	Model (D/E)		Government with academia and industry	
MODEL SOFC OPERATION (START UP, PART LOAD, SHUT DOWN)	Establish off-design conditions and requirements (E)		Industry with government	none
,	Development coupled transient models (D/E)		Government with academia	
	Validate model (D/E)		Government with industry	
		• Integration with design cycle (E)	Industry	
		 Accommodate technology breakthroughs (D/E) 	Government with Academia and industry	

Key: E = Engineering

D = Development

R = Research

Modeling and Simulation: Report-Out

Issues	R&D Opportunities	ACTIONS
System modeling Total life cycle cost performance analysis optimization Stack Models lack of suitable multi-physics engineering models (thermal, electrochemical, transport coupling) Cross-cutting Issues Validation/benchmark data for models	Stack computational Coupled multi-dimensional Multi-physics engineering model (with benchmark problem set) Cell Computational Fundamental models (multi-dimensional) with emphasis on: ! Electrochemical ! Kinetic ! Transport aspects Benchmarks - Characterize cell design - Obtain detail test data - Develop model	Models for Cell /stack 1 0-5 Years, Evaluate existing models, G/I 1 0-5 Develop electrochemical, kinetic, models G/I 1 0-5, Application models for SECA vision G/I 1 0-5, Incorporate into system Model G/I 1 5-10 Refine models (for tech. Breakthroughs) G/I 1 5-10 Raket-specific models G/I 1 5-10 Reduce turnaround time to speed design cycle G/I Benchmark 1 0-5 Develop/characterize benchmark cells G 1 0-5 Test and provide detailed data G/A 1 0-5 Model development G/A/I SOFC Operation Model 1 0-5 Establish off-design conditions/requirements I 1 0-5 Develop transient model G 1 0-5Validate model G/I 1 5-10 Integrate with design cycle I 1 5-10 Accommodate technical breakthrough G

Key: I = Industry G = GovernmentA = Academia

VI. Power Electronics Group Summary

Issues

The following issues received the most votes:

- Complex system interface
- Modular family architecture
- Poor load following
- Use of SiC silicon carbide
- Cooling thermal management
- Lifetime
- Cost discrepancy

Opportunities

The R&D opportunities were categorized into four header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

Thermal Management

Higher temperature components, e.g., capacitors

Interface

- Integrated devices
- Systems dynamic modeling

Cost

• DFMA –design for manufacture and assembly

Reliability

• Improve component materials

Actions

By combining the component opportunities, actions were developed for the top two opportunities.

Integrated Devices Interface:

- Align with manufacturer
- Develop open architecture for common module hardware and software toolkits

- Identify common denominators from developers across applications
- Assess packaging interconnections
- Develop codes and standards across industries
- Develop communication protocols
- Develop predictive controls

Components Reliability and Thermal Management:

- All components need to be better, faster, smaller, and cheaper
- Re-engineer capacitor
- Improve higher temperature capabilities for connections, solder, circuit boards, and substrate
- Improve switching characteristics with lower losses and higher temperature
- Improve heat sink integrated thermal management

POWER ELECTRONICS

PARTICIPANTS

NAME	AFFILIATION
Don Adams, Chairperson*	Oak Ridge National Lab
Thom Broe	Sustainable Energy Technology
T.P. Chen	Nexant, Inc.
Michel Jullian	OCM Technology
John Kalmakoff	Sustainable Energy Technologies
Benson P. Lee	Technology Management, Inc.
Hans Maru	FuelCell Energy, Inc.
Don McConnell	Pacific Northwest National Lab
Tim McDonald	Pinnacle West Capital Corp (APS)
Tim McIntyre	Oak Ridge National Lab
Steve Satzberg	Office of Naval Research
Tim Theiss	Oak Ridge National Lab
Mark Williams	NETL
FACILITATOR: Kevin Moore	Energetics, Incorporated

^{*} = Presenter for report-out

Power Electronics: What Are the Scientific and Technical Issues to Achieve SECA Vision by 2010?

INTERFACE	TOPOLOGY	RELIABILITY	Соѕт
 Domain vs. stationary Synchronize to grid kk Complex system interface kkkkkk Dynamic range System inverter ganging Output power quality BOP – Balance of Plant Modular family architecture kkkkk Integrated controls DC chopper Programability on fly Remote dispatch Black start Lousy load following kkkkk 	 Switches topology k Passive components k SiC – Silicon Carbide kkk 	Cooling thermal management kkkkk Graceful degradation Noise control Lifetime kkkkk Telemetry remote diagnostics	Size, volume, and weight kk Economies of scale Cost discrepancy kkk

Power Electronics: What Are the R&D Opportunities to Overcome Issues to SECA?

THERMAL MANAGEMENT	Interface	Соѕт	RELIABILITY
Higher temperature components, e.g., capacitors KKKKK Direct cooling of silicon or SiC K Cheap diamond film Integrated electronic within cell K	 Definition of system requirements kk Load prediction Establish standards Challenge 5 kW choice Plug and Play kk Low cost storage high density caps Systems dynamics modeling kkk Functional tradeoff studies Integrated devices kkkkkk Ganging inverters 	Cost tradeoffs studies k Soft switching topology Integrated devices kk Manufacturing process development DFMA kkkk Grid interconnect standards Packaging of PE module	Improve component materials KKKKK Prognostics Topology choice, e.g., redundancy, multi-level K Robust design K Soft failure

Power Electronics: What Actions to Take Advantage of R&D Opportunities?

R&D OPPORTUNITY	ACTIONS 0-5 YEARS	Type of Action	ACTIONS 5-10 YEARS	Type of Action	LEAD ROLES
Integrated Devices "Interface"	Align with manufacturer	Е			Industry
! Board or chip module! Fuel cell electronics with	Develop open architecture for common module hardware and software toolkits	E,D			Industry, University, Government
power electronics ! Transformerless design	Identify common denominators from developers across applications	Е			University, Government
! PE-DC Bus in box; PE- AC-Grid outside	Packaging interconnections	E,D,R			Industry, University, Government
	Develop codes and standards across industries	Е			Government, University, Industry
	Communication protocols	E,D			Government, University, Industry
	Predictive controls	E,D,R			Government, University, Industry
Improve Component Materials "Reliability" and	Better, faster, smaller, cheaper	D,R	Better, faster, smaller, cheaper	E,D	Government, University, Industry
Higher Temperature Components, "Thermal	Re-engineer capacitor	R	Re-engineer capacitor		Government, University, Industry
Manage" ! Capacitors-inductors ! Connections ! Switch ! Solder	Higher temperature capabilities Connections Solder Circuit Boards Substrate	D,R	Higher temperature capabilities	E,D	Government, University, Industry
! Circuit boards ! Substrates ! Heat sinks	Switch Improved switching characteristics Lower losses Higher temperature	D,R	Switch	E,D	Government, University, Industry
	Heat sink-integrated thermal management	D,R	Heat sink	E,D	Government, University, Industry

Key: E = Engineering

D = Development

R = Research

Power Electronics: Report-Out

POWER ELECTRONICS	Issues	R&D OPPORTUNITIES	ACTIONS
Is power electronics in the fuel cell "box" or not? Ganged 5 kW modules are not practical for power electronics? Status ' \$7/kW mobile in 3 years 90+% efficiency Air-cooled industrial drives	Complex system interface Modular family architecture Lousy load following Thermal management Lifetime	Integrated devices for interface Reliability – improve component materials Thermal Management – higher temperature components	Integrated devices Integrated devices Index and software Index are Index are Integrated Experiments Index are Interest Integrated Experiments Integrated devices Integrated devices Integrated devices Integrated devices Integrated devices Integrated Hardware and software Integrated Hardware and software and software Integrated devices Integrated device

VII. THERMAL SYSTEMS GROUP SUMMARY

Issues

The following issues received the largest number of votes:

- Thermal enclosure
- Water recovery system
- Air pre-heater cost/performance trade-off
- Excessive heat losses in small high temperature systems
- Afterburner pre-heater
- Waste heat utilization (power generation/co-generation)
- Transient stresses during normal and abnormal events (loss of cooling air)
- Start-up overall speed

Opportunities

The R&D opportunities were categorized into five header topics. The following are the header topics and the corresponding R&D opportunities that received a multiple number of votes:

Water Management Strategy

Designs using recycled steam

Air Preheater

- Materials and fabrication
- Integrated catalytic combustion
- Configuration optimize design

Overall Startup Speed

- Reduce thermal capacitance
- Optimize idle mode strategies

Transient Stresses During Normal and Abnormal Events

Dynamic modeling (transient)

Thermal Enclosure: Material, Design, & Cost

- Better insulating materials
- Optimize compartment design

<u>Actions</u>

Due to time constraints, only two of the highest priority opportunities could be analyzed.

Water Management - Designs Using Recycled Steam:

- System study of onsite/onboard water vs. recycle steam
- Develop designs for water recovery
- Prototype water recovery
- Research ways to recover water without phase change
- Develop design without phase change
- Prototype without phase change

Thermal Enclosure – Better Insulating Materials:

- Optimize design of the compartment
- Study family of applicable materials and select material
- Prototype

THERMAL SYSTEMS

PARTICIPANTS

Name	Affiliation
Sy Ali	Rolls-Royce Corporation
Richard A. Bajura	West Virginia University (NRCCE)
Mike Binder	U.S. Army CERL
Claude Cahen	Unicom Distributed Energy
Minking K. Chyu	University of Pittsburgh (Mechanical Engineering)
Jim Conklin	Oak Ridge National Laboratory
Romesh Kumar, Chairperson	Argonne National Laboratory
Bob Lorand	SAIC
Irven Miller	I.B. Miller, Inc.
Eric Simpkins	FuelCell Energy Inc.
Joe Strakey	DOE/NETL
Larry Van Bibber*	SAIC
Ed Yarbrough	Honeywell
FACILITATOR: Alicia R. Dalton	Energetics, Incorporated

^{* =} Presenter for report-out

Thermal Systems: What Are the Issues (Science and Technology) to Achieving the Vision?

 $(\mathbf{k} = \text{Vote for Priority Topic})$

OTHER	COMPONENTS	Integration	OPERATING STRATEGIES
Sulfur in fuel creates many of the thermal system issues	Materials No high temperature recycle blower available to recycle anode exhaust back to inlet to provide water Thermal enclosure Materials Design Cost Kkkkkk Catalyst and housing material selection driven by temperature Air preheater cost/ performance trade off kkk Air preheater: need high active heat exchange surface area per unit active volume/weight kk Water Recovery System Kkkk Seals) Maintaining system integrity due to temperature gradients in space and time kk Nox (Emissions) governed by temperature	Excessive heat losses in small high temperature systems kkkk Using afterburner as startup k Waste heat utilization (power generation/cogeneration) kkk Reformer/Stack k Afterburner/Preheater kkkk Air cooled fuel cell stack is too difficult to manage Temperature gradients with air flow uniformity, maintenance (Seals) Maintaining system integrity due to temperature gradients in space and time kk NOx (Emissions) governed by temperature	Designing for extremes k Transient stresses during normal and abnormal events (loss of cooling air) KKKKK Thermal/overall operator training, diagnostics Temperature/flow control system KK Startup ! Overall speed KKKKK ! Thermal Human Safety ! Noise ! Emissions ! Heat Air cooled fuel cell stack is too diffi cult to manage Temperature gradients with air flow uniformity, maintenance

Thermal Systems: What Are the R&D Opportunities to Overcome the Issues?

 $(\mathbf{k} = \text{Vote for Priority Topic})$

WATER MANAGEMENT STRATEGY	AIR PREHEATER	OVERALL STARTUP SPEED	TRANSIENT STRESSES DURING NORMAL AND ABNORMAL EVENTS	THERMAL ENCLOSURE: MATERIALS, DESIGN, & COST
 Optimize design Designs using recycled steam KKKKK Misc. – Water for fuel processor 	Configuration – optimize design	Reduce thermal capacitance kkkk Optimize idle mode strategies kkk Develop robust hardware design kk	Ceramics – improve, toughened kk Improve hardware design k Dynamic modeling (transient) kkkk Controls design k	Better insulating materials kkkkk Cheaper materials kk Optimize compartment design kkkk

Thermal Systems: What Are the Actions to Take Advantage of the R&D Opportunities

OPPORTUNITY -	ACTION	ACTION TYPE	TIMEFRAME	LEADER	OTHER FACTORS
WATER MANAGEMENT					
- Designs Using	System study onsite/onboard water vs.	Е	6 mo.	DOE/DoD	
RECYCLED STEAM	recycle steam				
	Develop designs for water recovery	E	18 - 24 mos.	Core Tech	
	Prototype (water recovery)	E	1 – 3 yr (parallel to research)	Industry	
	Research ways to recover water without phase change	R	1 – 3 yr	Core Tech	
	Develop design (without phase change)	E	1 - 3 yr	Core Tech	
	Prototype (without phase change)	E	1 − 3 yr	Industry	
OPPORTUNITY -	ACTION	ACTION TYPE	TIMEFRAME	LEADER	OTHER FACTORS
THERMAL ENCLOSURE	Optimize Design	Е	1 – 2 yr.	Industry	Note: What must be in the box?
- BETTER INSULATING					1 – Main box design2 – Feed platelets
Materials	Study family of applicable materials Select Material	D	6 mos. – 1 yr.	Core Tech	
	Prototype	E	1 – 2 yr.	Industry	

Key: E = Engineering
D = Development

R = Research

Thermal Systems – Report Out

(**k** = Vote for Priority Topic)

THERMAL SYSTEMS	Issues	Opportunities	
Thermal Systems What are they? Everything Else Air Preheater I After burner Hermal enclosure H2O management Et al. Could be the Achilles Heel	 Categories ! Components ! Operating Strategies ! Integration Top Vote Getters ! Thermal enclosure	Categories Air preheater Overall startup speed Transients Stresses Thermal enclosure H ₂ O Management Strategies Top Vote Getters Design of H2O management system using recycled steam kkkkkk Better insulating materials for thermal enclosure kkkkk Kkkk Optimize compartment design kkkk Air preheater materials and fabrication kkkk Integrated catalytic combustor with air preheater kkkk Reduced thermal capacitance kkkk Reduced thermal capacitance kkkk Dynamic modeling kkkk Dynamic modeling kkkk	

OPPORTUNITY	ACTIONS	TIMEFRAME	LEAD	Other
Water Management Designs Using Recycled Steam	System Study: (E) On board Water vs. Recycle Steam	6 months	DOE/DoD	
	Develop Designs for Water Recovery (E)	18 - 24 months	Core Tech	
	Prototype (E) (water recovery)	1 – 3 years	Industry	
	Research Ways to Recovery Water Without Phase Change (R)	1 – 3 years (parallel to above)	Core Tech	
	Develop Design (E) (without phase change)	1 – 3 years	Industry	
	Prototype (E) (without phase change)	1 – 3 years		
Thermal Enclosure – Better Insulating Materials	Optimize Design	1 – 2 years	Industry	What must be in the box? Main box Feed platelets
	Study Family of Applicable Materials Select Material	6 mos. – 1 year	Core Tech	
	Prototype	1 – 2 years	Industry	

Key: E = Engineering

D = Development

R = Research

APPENDIX B **PARTICIPANTS**

1 Jeff Abboud

Fuel Cell Power Association

P.O. Box 7574

Arlington, VA 22207 Phone: 703/623-0698 Fax: 703/536-1927

E-mail: abboud@advocatesinc.com

Donald J. Adams

Oak Ridge National Laboratory

Bear Creek Road

P.O. Box 2009, MS 8038 Oak Ridge, TN 37831 Phone: 865/576-0260

865/241-6124 Fax: E-mail: adamsdj@ornl.gov

Gerald Daniel Agnew

Rolls-Royce PLC

P.O. Box 31

Derby, United Kingdom, DE24 8BJ Phone: 011 441 332 269 181 Fax: 011 441 332 248 000

E-mail: gerry.agnew@rolls-royce.com

Said Al-Hallaj

IIT - Chicago

10 West 33rd Street

Chicago, IL 60616

Phone: 312/567-5118 Fax: 312/567-6914

E-mail: alhasai@charlie.cns.iit.edu

Sy A. Ali

Rolls-Royce Corporation

P.O. Box 420

Indianapolis, IN 46206-0420

Phone: 317/230-6864 Fax: 317/230-2900 E-mail: sy.a.ali@allison.com

K. R. (Ammi) Amarnath

EPRI Solutions, Inc.

3412 Hillview Avenue

Palo Alto, CA 94304

Phone: 650/855-2548 Fax: 650/855-8574 E-mail:

aamarnat@epri.com

Harlan U. Anderson

University of Missouri at Rolla 303 Materials Research Center

Rolla, MO 65401

Phone: 573/341-4886 573/341-6151 Fax: E-mail: harlanua@umr.edu

David H. Archer

Carnegie Mellon University

114 Kentzel Road

Pittsburgh, PA 15237-2816 Phone: 412/268-6808

Fax: 412/268-3348

E-mail: archerdh@andrew.cmu.edu

Tim Armstrong

Oak Ridge National Laboratory

1 Bethel Valley Road

Mailstop 6084

Oak Ridge, TN 37831-6084

Phone: 865/574-7997

Fax: 865/574-4357

E-mail: armstrongt@ornl.gov

Rita A. Bajura

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4511 Fax: 304/285-4292

E-mail: rita.bajura@netl.doe.gov

Richard A. Bajura

West Virginia University

NRCCE

P.O. Box 6064

Morgantown, WV 26506-6064 Phone: 304/293-2867 x 5401 304/293-3749 Fax:

E-mail: bajura@wvu.edu

12. William Barker

ITN Energy Systems, Inc. 12401 West 49th Avenue Wheat Ridge, CO 80033 Phone: 303/420-3646 Fax: 303/285-5162 E-mail: wbarker@itnes.com

13. Scott Barnett

Northwestern University
Materials Science Dept.
Evanston, IL 60208
Phone: 847/491-2447
Fax: 847/491-7820
E-mail: s-barnett@nwu.edu

14. James T. Bartis

Rand

1200 South Hayes Mailstop 6150

Arlington, VA 22202-5050
Phone: 703/413-1100 x 5317
Fax: 703/413-8111
E-mail: bartis@rand.org

15. Michael Batham

California Energy Commission

1516 Ninth Street Mailstop 43

Sacramento, CA 95814-5512 Phone: 916/654-4548 Fax: 916/653-6010

E-mail: mbatham@energy.state.ca.us

16. David R. Bauer

Mailstop SRL-3182 P.O. Box 2053 Dearborn, MI 48121 Phone: 313/594-1756 Fax: 313/323-1129

Ford Motor Company

Fax: 313/323-1129 E-mail: dbauer3@ford.com

17. Donald F. Beal

Performance Ceramics Company

2346 Major Road Peninsula, OH 44264 Phone: 330/657-2884 Fax: 330/657-2226

E-mail: dfb@performanceceramics.com

18. Ray Benn

United Technologies Research Center

411 Silver Lane

East Hartford, CT 06108

Phone: 860/610-7772

Fax: E-mail:

Glen Benson

Aker Industries, Inc. 952 - 57th Street

Oakland, CA 94608-2842 Phone: 510/658-7248 Fax: 510/658-7292

E-mail: jkerindustries@hotmail.com

20. David A. Berry

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4430 Fax: 304/285-4469 E-mail: dberry@netl.doe.gov

21. Ed Beyma

Parsons Corporation 19644 Club House Road Gaithersburg, MD 20886 Phone: 301/869-9191 Fax: 301/977-7507

E-mail: ed.f.beyma@parsons.com

22. Michael J. Binder

U.S. Army CERL

P.O. Box 9005

Champaign, IL 61826-9005 Phone: 217/373-7214 Fax: 217/373-6740

E-mail: m-binder@cecer.army.mil

23. David Lee Black

CFD Research Corporation

215 Wynn Drive Huntsville, AL 35805 Phone: 256/726-4874 Fax: 256/726-4806 E-mail: dlb@cfdrc.com

24. Jeff Bolebruch

Blasch Precision Ceramics

580 Broadway Albany, NY 12204

Phone: 518/436-1263 x 42 Fax: 518/436-0098

E-mail: jbolebruch@blaschceramics.com

25. Brian Borglum

Siemens Westinghouse Power Corp.

1310 Beulah Road Pittsburgh, PA 15235

Phone: 412/256-1696 Fax: 412/256-5504

E-mail: brian.borglum@swpc.siemens.com

26. Damon Bresenham

Generac Power Systems, Inc.

P.O. Box 8

Waukesha, WI 53187

Phone: 262/544-4811 x 2125

Fax: 262/544-4851

E-mail: dbresenham@generac.com

27. Thomas Kenneth Broe

Sustainable Energy Technology

1520 4th Street, S.W.

Suite 850

Calgary, Alberta, Canada, T2R 0Y4

Phone: 403/508-7177 Fax: 403/205-2509

E-mail: broe@sustainableenergy.com

28. Jacob Brouwer

National Fuel Cell Research Center University of California, Irvine

131 ELF

Irvine, CA 92697-3550
Phone: 949/824-1999x221
Fax: 949/824-7423
E-mail: jb@nfcrc.uci.edu

29. Claude Cahen

Unicom Distributed Energy 2315 Enterprise Drive Westchester, IL 60154 Phone: 708/236-8071 Fax: 708/236-8051

E-mail: claude.cahen@ucm.com

30. Richard T. Carlin

Office of Naval Research 800 North Quincy Street Arlington, VA 22217-5660 Phone: 703/696-5075 Fax: 703/696-6887 E-mail: carlinr@onr.navy.mil

31. Ann Cecchetti

Battelle - PNNL

10420 Greenacres Drive Silver Springs, MD 20903

Phone: 202/646-5228 Fax: 202/646-7833 E-mail: acecchetti@aol.com

32. Ismail B. Celik

West Virginia University

Mechanical & Aerospace Engineering

P.O. Box 6101

Morgantown, WV 26506-6106

Phone: 304/293-3111 Fax: 304/293-6689

E-mail: icelik@cemr.wvu.edu

33. Ravi Chandran

MTCI

6001 Chemical Road Baltimore, MD 21226 Phone: 410/354-0420 x 16 Fax: 410/354-9894

E-mail: rchandran@mtcionline.net

34. Denise Chen

NSWC Carderock 5001 S. Broad Street

Philadelphia, PA 19112-5083 Phone: 215/897-8650 Fax: 215/897-7874

E-mail: chend@nswccd.navy.mil

35. Tan-Ping Chen

Nexant, LLC

45 Fremont Street

San Francisco, CA 94105-2210

Phone: 415/768-1419
Fax: 415/768-3580
E-mail: tpchen@nexant.com

36. C. P. Chen

University of Alabama in Huntsville EB 130, Chemical Engineering Huntsville, AL 35899

Phone: 256/890-6194

Fax:

E-mail: cchen@che.uah.edu

37. Larry Chick

Pacific Northwest National Laboratory

Mailstop K2-44 P.O. Box 999 Richland, WA 99352

Phone: 509/375-2145 Fax: 509/375-2186 E-mail: larry.chick@pnl.gov 38. Minking K. Chyu

University of Pittsburgh

648 Benedum Hall

Pittsburgh, PA 15261

Phone: 412/624-9783 Fax: 412/624-4846

E-mail: mkchyu@engrng.pitt.edu

39. Michael A. Cobb

Michael A. Cobb & Company

1688 Brookwood Drive

Akron, OH 44313-5068

Phone: 330/869-8046 Fax: 330/869-8058

E-mail: cobbcomp@aol.com

40. James Conklin

Oak Ridge National Laboratory

Building 9108

P.O. Box 2009, MS 8088

Oak Ridge, TN 37831

Phone: 865/574-0567

865/574-2102 Fax:

E-mail: conklinjc@ornl.gov

41. Thomas B. Dade

Newport News Shipbuilding

4101 Washington Avenue

Building 600-1, Dept. E86

Newport News, VA 23607

Phone: 757/688-0723

Fax:

757/688-1073 E-mail: dade_tb@nns.com

42. Alicia R. Dalton

Energetics

2414 Cranberry Square

Morgantown, WV 26508

Phone: 304/594-1450

Fax: 304/594-1485

E-mail: alicia.dalton@netl.doe.gov

43. Sandy J. Dapkunas

NIST

100 Bureau Drive

Bldg. 223, Room A256

Gaithersburg, MD 20899-8520

Phone: 301/975-6119

Fax: 301/975-5334

E-mail: sandy_dapkunas@ta.doc.gov Pat Davis

U.S. Department of Energy

1000 Independence Ave., S.W.

Mailstop EE-32

Washington, DC 20585

Phone: 202/586-8061

Fax: 202/586-9811

E-mail: patrick.davis@ee.doe.gov

45. William J. Dawson

NexTech Materials, Ltd.

720-I Lakeview Plaza Blvd.

Worthington, OH 43085-4733

Phone: 614/842-6606

Fax: 614/842-6607

E-mail: dawson@nextechmaterials.com

Lutgard C. DeJonghe

University of California at Berkeley

Lawrence Berkeley National Lab

1 Cyclotron Road, MS Bldg. 62-203

Berkeley, CA 94720

Phone: 510/486-6138

Fax: 510/486-4881

E-mail: dejonghe@lbl.gov

47. Richard A. Dennis

National Energy Technology Laboratory

U.S. Department of Energy

3610 Collins Ferry Road

Morgantown, WV 26507-0880

Phone: 304/285-4515

Fax: 304/285-4403

E-mail: rdenni@netl.doe.gov

48. John Deur

ADAPCO

60 Broadhollow Road

Melville, NY 11747

Phone: 631/549-2300

Fax: 631/549-2654

E-mail: jdeur@adapco.com

49. Duane Dimos

Sandia National Labs

P.O. Box 5800

Albuquerque, NM 87185-0756

Phone: 505/844-6385

Fax: 505/844-9781

E-mail: dbdimos@sandia.gov

50. Herbert H. Dobbs

U.S. Army TACOM

34461 Arundel

Warren, MI 48397-5000 Phone: 810/574-4228

Fax: 810/574-4244

E-mail: dobbsh@tacom.army.mil

51. Gregory Dolan

U. S. Fuel Cell Council 1625 K Street, N.W.

Suite 725

Washington, DC 20006
Phone: 202/293-5500
Fax: 202/785-4313
E-mail: gdolan@usfcc.com

52. Richard Dye

U.S. Department of Energy 1000 Independence Avenue, S.W. Mailstop FE-26

Washington, DC 20585 Phone: 202/586-6499 Fax: 202/586-7085

E-mail: richard.dye@hq.doe.gov

53. Christopher J. Egan

U.S. Navy / NAVSEA

2531 Jefferson Davis Highway

Crystal Park, Suite 817

Arlington, VA 22242-5169
Phone: 703/604-6052 x 548
Fax: 703/604-6056

E-mail: egancj@navsea.navy.mil

54. Emile Ettedgui

Rand

1200 S. Hayes Street

Mailstop 6102

Arlington, VA 22202-5050
Phone: 703/413-1100 x 5427
Fax: 703/413-8111

Fax: /03/413-8111 E-mail: emile@rand.org

55. Peter Faguy

MicroCoating Technologies 3798 Green Industrial Way Chamblee, GA 30341

Phone: 678/300-3503 Fax: 678/530-9151

E-mail: pfaguy@microcoating.com

56. Samuel M. Fleming

INEEL

P.O. Box 1625

 Idaho Falls, ID
 83415-3898

 Phone:
 208/526-5877

 Fax:
 208/526-4563

 E-mail:
 flemsm@inel.gov

57. Chris Forbes

Siemens Westinghouse Power Corp.

1310 Beulah Road Pittsburgh, PA 15235 Phone: 412-256-2022 Fax: 412-256-1233

E-mail: christian.forbes@swpc.siemens.com

58. Lyman J. Frost

INEEL

Mailstop 3805 P.O. Box 1625

 Idaho Falls, ID
 83415

 Phone:
 208/526-2941

 Fax:
 208/526-0876

 E-mail:
 frosl@inel.gov

59. Rodney A Geisbrecht

National Energy Technology Laboratory

U.S. Department of Energy 626 Cochrans Mill Road Pittsburgh, PA 15236-0940 Phone: 412/386-4870

Fax: 412/386-4604 E-mail: rgeisb@netl.doe.gov

60. Randall S. Gemmen

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4536
Fax: 304/285-4403
E-mail: rgemm@netl.doe.gov

61. Tom J. George

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4825 Fax: 304/285-4403

E-mail: tom.george@netl.doe.gov

62. Robert Glass

Lawrence Livermore National Laboratory

7000 East Avenue

MS L-644

Livermore, CA 94550
Phone: 925/423-7914
Fax: 925/423-7914
E-mail: glass3@llnl.gov

63. Raymond Gorte

University of Pennsylvania 311 Towne Building 220 S. 33rd Street Philadelphia, PA 19104

Phone: 215/898-4439 Fax: 215/573-2093

E-mail: gorte@seas.upenn.edu

64. M. James Grieve

Delphi Automotive Systems

21 Wenlock Road Fairport, NY 14450 Phone: 716/359-6253 Fax: 716/359-6896

E-mail: m.james.grieve@delphiauto.com

65. Manoj K. Guha

American Electric Power Service Corp.

*1 Riverside Plaza

Columbus, OH 43215-2373
Phone: 614/223-1285
Fax: 614/223-2112
E-mail: mkguha@aep.com

66. Douglas Gyorke

National Energy Technology Laboratory

U.S. Department of Energy 626 Cochrans Mill Road Pittsburgh, PA 15236-0940 Phone: 412/386-6173 Fax: 412/386-4775 E-mail: gyorke@netl.doe.gov

67. Sossina M. Haile

California Institute of Technology 1200 E. California Boulevard

Mailstop 138-78
Pasadena, CA 91125
Phone: 626/395-2958
Fax: 626/578-0058
E-mail: smhaile@caltech.edu

68. Buddy Hartberger

U.S. Coast Guard

2100 Second Street, S.W. Washington, DC 20593-0001

Phone: 202/267-0886 Fax: 202/267-2598

E-mail: ahartberger@comdt.uscg.mil

69. Comas Haynes

Georgia Tech

514 Ridgecreek Drive

Clarkston, GA 30021

Phone: 404/894-1012 Fax: 404/894-8336

E-mail: ch135@prism.gatech.edu

70. Jack Hirschenhofer

Parsons Corporation

4 Goldfinch Drive

Wyomissing, PA 19610

Phone: 610/777-4036 Fax: 610/855-2384

E-mail: john_h_hirschenhofer@parsons.com

71. Diane Hooie

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4524
Fax: 304/285-4216
E-mail: dhooie@netl.doe.gov

72. Kevin Huang

University of Texas at Austin 26th Street and San Jancinto

ETC 9102

Austin, TX 78712-1063 Phone: 512/471-3588 Fax: 512/471-7681

E-mail: kqhuang@mail.utexas.edu

73. Wayne Huebner

University of Missouri at Rolla

222 McNutt Hall Rolla, MO 65401

Phone: 573/341-4401 Fax: 573/341-6934 E-mail: huebner@umr.edu 74. Zohair Ismail

CECOM

10108 Gridley Road

Suite 1

Ft. Belvoir, VA 22060 Phone: 703/704-2634 Fax: 703/704-3794

E-mail: zohair-k-ismail@belvoir.army.mil

75. Brian D James

Directed Technologies, Inc.

3601 Wilson Blvd.

Suite 650

Arlington, VA 22203 Phone: 703/243-3383 Fax: 703/243-2724

E-mail: brian-james@directedtechnologies.com

76. Lisa A. Jarr

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4555 Fax: 304/285-4292

E-mail: lisa.jarr@netl.doe.gov

77. Roddie R. Judkins

Oak Ridge National Laboratory

1 Bethel Valley Road

Mailstop 6084

Oak Ridge, TN 37831-6084 Phone: 865/574-4572 Fax: 865/574-4357 E-mail: judkinsrr@ornl.gov

78. Michel Jullian

OCM Technology, Inc. 2183 Thurston Drive

Ottawa, Ontario Canada, K1G 6C9

Phone: 613/736-5665 Fax: 613/736-5525

E-mail: michel.jullian@ocmtech.com

79. Johnny Kalmakoff

Sustainable Energy Technology

Alberta Place Suite 850

Calgary, Alberta, Canada, T2R 0Y4

Phone: 403/508-7177 Fax: 403/205-2509

E-mail: kalmakoff@sustainableenergy.com

80. Darrell Kent

OCM Technology, Inc. 2333 Springfield Circle

Oakville, Ontario, Canada, L6J7P8

Phone: 905/829-8899 Fax: 905/829-0688

E-mail: kentdsmithj@sprint-com

81. Moe A. Khaleel

Pacific Northwest National Laboratory

P.O. Box 999 MS K2-18

Richland, WA 99352

Phone: 509/375-2438 Fax: 509/375-6605

E-mail: moe.khalee1@pnl.gov

82. Kevin Krist

Gas Research Institute 8600 West Bryn Mawr Ave.

Chicago, IL 60631

Phone: 773/399-8211 Fax: 773/399-8170 E-mail: kkrist@gri.org

83. Bill Krusel

PACCAR, Inc.

27260 Haggerty Road

Suite A-7

Farmington Hills, MI 48331

Phone: 248/553-2347 Fax: 248/553-3821

E-mail: bill.krusel@paccar.com

84. Romesh Kumar

Argonne National Laboratory 9700 South Cass Avenue

MS D-205

Argonne, IL 60439-4837 Phone: 630/252-4342

Fax: 630/252-4176 E-mail: kumar@cmt.anl.gov

85. Jerome LaMontagne

Brookhaven National Laboratory

12 North Sixth Street

Building 526

Upton, NY 11973

Phone: 631/344-2831 Fax: 631/344-2359

E-mail: jerome@bnl.gov

86. Benson P. Lee

Technology Management, Inc.

9718 Lake Shore Blvd.

Cleveland, OH 44108

Phone: 216/541-1000 Fax: 216/541-1000 E-mail: tmi@stratos.net

87. John Leeper

Southern California Edison 2244 Walnut Grove Avenue

Rosemead, CA 91770

Phone: 626/302-8936 Fax: 626/302-8030 E-mail: leeperjd@sce.com

88. Werner Lehnert

Adam Opel AG

1 PC-81-90

Russelsheim, Germany, D-65423

Phone: 49 6142 765773 Fax: 49 6142 766151

E-mail: werner.lehnert@de.opel.com

89. David Lewis

Argonne National Laboratory

9700 South Cass Avenue

Building 205

Argonne, IL 60439

Phone: 630/252-4383 Fax: 630/252-5528 E-mail: lewisd@cmt.anl.gov

90. Jason T. Lewis

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4724 Fax: 304/285-4403

E-mail: jason.lewis@netl.doe.gov

91. Craig A. Linne

Visteon Corporation

15041 Commerce Drive S.

Suite 401

Dearborn, MI 48120
Phone: 313/845-8984
Fax: 313/323-8132
E-mail: clinne@visteon.com

92. Meilin Liu

Georgia Tech

778 Atlantic Drive

MS-0245

Atlanta, GA 30332-0245 Phone: 404/894-6114 Fax: 404/894-9140

E-mail: meilin.liu@mse.gatech.edu

93. Ronald E. Loehman

Sandia National Labs

Advanced Materials Lab

1001 University Blvd., SE, Suite 100

Albuquerque, NM 87106 Phone: 505/272-7601 Fax: 505/272-7304

E-mail: loehman@sandia.gov

94. Bob Lorand

Science Applications International Corp.

8301 Greensboro Drive

Mailstop E-4-6 McLean, VA 22102 Phone: 703/676-4439

Fax: 703/356-4056

E-mail: robert.t.lorand@saic.com

95. Howard Lowitt

Energetics, Inc.

7164 Columbia Gateway Drive

Columbia, MD 21046

Phone: 410/290-0370 x 249 Fax: 410/423-2195

E-mail: hlowitt@energetics.com

96. Bill Luecke

NIST

100 Bureau Drive

MS 8521

Gaithersburg, MD 20899-8521

Phone: 301/975-5744 Fax: 301/975-5334

E-mail: william.luecke@nist.gov

97. Momtaz N. Mansour

ThermoChem, Inc. 6001 Chemical Road

Baltimore, MD 21226 Phone: 410/354-9890 x 12

Fax: 410/354-9894

E-mail: mmansour@tchem.net

98. Scott X. Mao

University of Pittsburgh 3700 O'Hara Street

Dept. of Mechanical Engineering

Pittsburgh, PA 15261 Phone: 412/624-9602 Fax: 412/624-4846

E-mail: smao@engrng.pitt.edu

99. James A. Marsh

Concurrent Technologies Corporation

3610 Collins Ferry Road Morgantown, WV 26505 Phone: 304/285-4064 Fax: 304/285-4403

E-mail: jmarsh@netl.doe.gov

hmaru@fce.com

100. Hans Maru

FuelCell Energy, Inc.
3 Great Pasture Road
Danbury, CT 06813
Phone: 203/825-6006
Fax: 203/825-6273

101. Gary J. Mayo

E-mail:

Visteon Corporation 15041 Commerce Drive S.

Suite 401

Dearborn, MI 48120 Phone: 313/594-2147 Fax: 313/322-9856

E-mail: gmayo@visteon.com

102. Marshall Mazer

McDermott/Babcock & Wilcox 1820 N. Fort Myer Drive

Suite 804

Arlington, VA 22209 Phone: 703/351-6313 Fax: 703/351-6418

E-mail: marshall.mazer@mcdermott.com

103. Don McConnell

Pacific Northwest National Laboratory

902 Battelle Boulevard

P.O. Box 999

Richland, WA 99352 Phone: 509/372-6060 Fax: 509/372-4774

E-mail: mcconnel@battelle.org

104. Timothy McDonald

Pinnacle West Capitol Corp. (APS)

400 North 5th Street Mailstop 8931 Phoenix, AZ 85004

Phone: 602/250-3032 Fax: 602/250-3872

E-mail: timothy.mcdonald@pinnaclewest.com

105. Tim McIntyre

Oak Ridge National Laboratory

1 Bethel Valley Road Oak Ridge, TN 37831 Phone: 865/576-5402 Fax: 865/574-1249

E-mail:

106. Gary McVay

Pacific Northwest National Laboratory

902 Battelle Blvd.

P.O. Box 999, MSIN K2-50

Richland, WA 99352
Phone: 509/375-3762
Fax: 509/375-2167
E-mail: gary@pnl.gov

107. G. B. Kirby Meacham

Michael A. Cobb & Company

1688 Brookwood Drive Akron, OH 44313-5068

Phone: 330/869-8046
Fax: 330/869-8058
E-mail: cobbcomp@aol.com

108. James F. Miller

Argonne National Laboratory 9700 South Cass Avenue

MS CMT-205

Argonne, IL 60439-4837
Phone: 630/252-4537
Fax: 630/252-9505
E-mail: millerj@cmt.anl.gov

109. Carl E. Miller

Delphi Automotive Systems 4800 S. Saginaw Street Flint, MI 48501-1360 Phone: 810/257-7402 Fax: 810/257-7781

E-mail:

110. Irven Miller

I.B. Miller, Inc.

175 Washington Street

Long Branch, NJ 07740

Phone: 732/222-5783

Fax: 732/229-7708

E-mail: imiller@flakice.com

111. Nguyen Q. Minh

Honeywell

2525 W. 190th Street

Mailstop 36-1-93190

Torrance, CA 90504-6099

Phone: 310/512-3515

Fax: 310/512-3432

E-mail: nguyen.minh@honeywell.com

112. Bijoy K. Misra

Misra, Inc.

361 Whirlaway Court

Wheaton, IL 60187

Phone: 630/690-8570

Fax: 630/690-9467 E-mail: bkmisra@ziplink.net

113. Kevin Moore

Energetics

2414 Cranberry Square

Morgantown, WV 26508

Phone: 304/594-1450

Fax: 304/594-1485

E-mail: kevin.moore@netl.doe.gov

114. Michael Mundschau

Eltron Research, Inc.

4600 Nautilus Court South

Boulder, CO 80301-3241

Phone: 303/530-0263 x 134

Fax: 303/530-0264

E-mail: mundschau@eltronresearch.com

115. Jeff O. Neff

EG&G Technical Services, Inc.

3604 Collins Ferry Road

Suite 200, MS OO4

Morgantown, WV 26505-2353

Phone: 304/599-5941 X 111

Fax: 304/599-8904

E-mail: jneff@svcmgt.egginc.com

116. John A. Olenick

Advanced Refractory Technologies, Inc.

699 Hertel Avenue

Buffalo, NY 14207

Phone: 716/875-9543 x 202

Fax:

E-mail: jolenick@art-inc.com

117. Larry Osgood

Propane Education and Research Council

17560 Shiloh Pines Drive

Monument, CO 80132

Phone: 719/487-0080

Fax: 719/487-8802

E-mail: ldogood1@aol.com

118. David E. Parekh

Georgia Institute of Technology

7220 Richardson Road

Smyrna, GA 30080

Phone: 770/528-7826

Fax: 770/528-7019

E-mail: david.parekh@gtri.gatech.edu

119. Joseph F. Pierre

Siemens Westinghouse Power Corp.

1310 Beulah Road

Pittsburgh, PA 15235

Phone: 412/256-5313

Fax: 412/256-7233

E-mail: joseph.pierre@swpc.siemens.com

120. John Plunkett

EG&G Technical Services, Inc.

3610 Collins Ferry Road

P.O. Box 880, MS MO2

Morgantown, WV 26507-0880

Phone: 304/285-4605

Fax: 304/285-4488

E-mail: jplunk@netl.doe.gov

121. Michael T. Prinkey

Fluent, Inc.

3647 Collins Ferry Road

Suite A

Morgantown, WV 26505

Phone: 304/598-3770

Fax: 304/598-7185

E-mail: mtp@fluent.com

122. James Ralph

Argonne National Laboratory

9700 South Cass Avenue

Argonne, IL 60439-4837

Phone: 630/252-4519

Fax: 630/252-4176

E-mail: ralph@cmt.anl.gov

123. Udaya Rao

U.S. Department of Energy

National Energy Technology Laboratory

P.O. Box 10940

Pittsburgh, PA 15236-0940 Phone: 412/386-4743 Fax: 412/386-4604 E-mail: rao@netl.doe.gov

124. Dan Rastler

EPRI Solutions, Inc.

3412 Hillview Avenue

P.O. Box 10414

Palo Alto, CA 94304-1395

Phone: 650/855-2521
Fax: 650/855-8759
E-mail: drastler@epri.com

125. Carl Reiser

International Fuel Cells

195 Governors Highway

South Windsor, CT 06074

Phone: 860/727-2368 Fax: 860/727-2575

E-mail: reiserc@ifc.utc.com

126. Robert J. Remick

Institute of Gas Technology

1700 S. Mount Prospect Road

Des Plaines, IL 60018

Phone: 847/768-0560 Fax: 847/768-0916

E-mail: remick@igt.org

127. William A. Rogers

Fluent, Inc.

3647 Collins Ferry Road

Suite A

Morgantown, WV 26505

Phone: 304/598-3770 Fax: 304/598-7185

E-mail: war@fluent.com

128. Rhett Ross

Fuel Cells 2000

1625 K Street, N.W.

Suite 725

Washington, DC 20006

Phone: 202/785-4222

Fax: 202/785-4313

E-mail: rross@fuelcells.org

129. Richard Rozance

Car Sound Exhaust Systems, Inc.

22961 Arroyo Vista

Rancho Santa Margarita, CA 92688

Phone: 949/858-5900

Fax: 949/858-3600

E-mail:

130. George Rudins

U.S. Department of Energy

1000 Independence Ave., S.W.

Washington, DC 20585

Phone: 202/586-1650

Fax: 202/586-4085

E-mail: george.rudins@hq.doe.gov

131. Steve Satzberg

Office of Naval Research

800 North Quincy Street

Arlington, VA 22217-5660

Phone: 703/696-0946

Fax: 703/696-0308

E-mail: satzbes@onr.navy. mil

132. Chris Schilling

Ames Laboratory

Iowa State University

3161 Gilman

Ames, IA 50011

Phone: 515/294-9465

Fax: 515/294-8727

E-mail: schillin@iastate.edu

133. William P. Schweizer

McDermott Technology, Inc.

1562 Beeson Street

Alliance, OH 44601

Phone: 330/829-7507

Fax: 330/829-7293

E-mail: william.p.schweizer@mcdermott.com

134. Mohindar Seehra

West Virginia University

Physics Department

Hodges Hall

Morgantown, WV 26506-6315

Phone: 304/293-3422 x 1473

Fax: 304/293-5732 E-mail: mseehra@wvu.edu 135. Rajat K. Sen

Sentech, Inc.

4733 Bethesda Ave.

Suite 608

Bethesda, MD 20814
Phone: 301/654-7224
Fax: 301/654-7832
E-mail: rsen@sentech.org

136. Tim Sherwood

Philip Morris USA Philip Morris R&D P.O. Box 26583 Richmond, VA 23261

Phone: 804/274-3083 Fax: 804/274-4778

E-mail: tim.s.sherwood@pmusa.com

137. Dinesh K. Shetty

Materials & Systems Research, Inc.

5395 West 700 South Salt Lake City, UT 84104 Phone: 801/530-4987 Fax: 801/530-4820

E-mail: dshetty@materialsys.com

138. Eric Simpkins

FuelCell Energy, Inc.
3 Great Pasture Road
Danbury, CT 06813
Phone: 202/737-1372
Fax: 202/737-7337
E-mail: ercc@erols.com

139. Ron Sims

Ford Motor Company 2101 Village Road, MS 1170

P.O. Box 2053

Dearborn, MI 48121-2053
Phone: 313/594-0879
Fax: 313/248-5167
E-mail: rsims1@ford.com

140. Prabhakar Singh

Pacific Northwest National Laboratory

902 Battelle Blvd.

P.O. Box 999, MSIN K2-50

Richland, WA 99352 Phone: 509/375-5945

Fax: 509/375-2167

E-mail: prabhakar.singh.pnl.gov

141. Subhash C. Singhal

Pacific Northwest National Laboratory

Mailstop K2-18 P.O. Box 999

Richland, WA 99352
Phone: 509/375-6738
Fax: 509/375-6605
E-mail: singhal@pnl.gov

142. Harry Skruch

NAVSEA O5R

2531 Jefferson Davis Highway

MS 05R27

Arlington, VA 22242-5160 Phone: 703/602-0706 x 412 Fax: 703/602-0488

E-mail: skruchhj@navsea.navy.mil

143. Jack Solomon

Praxair Inc.

777 Old Saw Mill River Road Tarrytown, NY 10591-6714 Phone: 914/345-6442

Fax: 914/345-6486

E-mail: jack-solomon@praxair.com

144. Rengaswamy Srinivasan

The Johns Hopkins University 11100 Johns Hopkins Road Laurel, MD 20723-6099 Phone: 240/228-6378 Fax: 240/228-6904

145. Jeff Stevenson

E-mail:

Pacific Northwest National Laboratory

sriniri@jhuapl.edu

Mailstop K2-44 P.O. Box 999 Richland, WA 99352

Phone: 509/372-4697 Fax: 509/375-2186

E-mail: jeff.stevenson@pnl.gov

146. Joseph P. Strakey

National Energy Technology Laboratory

U.S. Department of Energy 626 Cochrans Mill Road Pittsburgh, PA 15236-0940 Phone: 412/386-6124

Fax: 412/386-4822

E-mail: joseph.starkey@netl.doe.gov

147. Larry D. Strickland

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road

Morgantown, WV 26507-0880

Phone: 304/285-4494
Fax: 304/285-4403
E-mail: lstric@netl.doe.gov

148. Wayne A. Surdoval

National Energy Technology Laboratory

U. S. Department of Energy
 626 Cochrans Mill Road
 Pittsburgh, PA 15236-0940
 Phone: 412/386-6002
 Fax: 412/386-4775

E-mail: surdoval@netl.doe.gov

149. Scott L. Swartz

Nextech Materials, Inc. 720-I Lakeview Plaza Blvd. Worthington, OH 43085-4733 Phone: 614/842-6606

Fax: 614/842-6606 Fax: 614/842-6607

E-mail: swartz@nextechmaterials.com

150. Walter G Taschek

CECOM

10108 Gridley Road

Suite 1

Ft. Belvoir, VA 22060 Phone: 703/704-1997 Fax: 703/704-3794

E-mail: wtaschek@hotmail.com

151. W. Peter Teagan

Arthur D. Little, Inc.

20 Acorn Park

Cambridge, MA 02140 Phone: 617/498-6054 Fax: 617/498-7206

E-mail: teagan.w@adlittle.com

152. Tim Theiss

UT-Battelle

1 Bear Creek Road Mailstop 8088

Oak Ridge, TN 37831
Phone: 865/574-1824
Fax: 865/241-1747
E-mail: theisstj@ornl.gov

153. Mike Thompson

Pacific Northwest National Laboratory

P.O. Box 999
Mailstop K7-50
Richland, WA 99352
Phone: 509/375-6471
Fax: 509/375-4481

E-mail: mike.thompson@pnl.gov

154. Edward Torrero

National Rural Electric Cooperative Association

4301 Wilson Blvd.

SS 9-204

Arlington, VA 22203
Phone: 703/907-5624
Fax: 703/907-5518
E-mail: ed.torrero@nreca.org

155. Matthew Tracy

Air Force Research Laboratory

2698 G Street

Wright Patterson AFB, OH 45433-7604

Phone: 937/255-8360 Fax: 937/255-6555

E-mail: matthew.tracy@wpafb.af.mil

156. Bruce R. Utz

National Energy Technology Laboratory

U.S. Department of Energy 626 Cochrans Mill Road Pittsburgh, PA 15236-0940 Phone: 412/386-5706 Fax: 412/386-5917

E-mail: bruce-utz@netl.doe.gov

157. Thomas I. Valdez

Jet Propulsion Laboratory 4800 Oak Grove Drive Mailstop 277-215 Pasadena, CA 91109 Phone: 818/354-3797 Fax: 818/393-6951

E-mail: thomas.i.valdez@jpl.nasa.gov

158. Lawrence E. Van Bibber

SAIC

P.O. Box 18689

Pittsburgh, PA 15236-0689 Phone: 412/386-4853 Fax: 412/386-4516

E-mail: vanbibb@netl.doe.gov

159. Jud Virden

Pacific Northwest National Lab

902 Battelle Blvd.

P.O. Box 999, MSIN K2-44

Richland, WA 99352

Phone: 509/375-6512 Fax: 509/375-2186

E-mail: jud.virden@pnl.gov

160. Anil V. Virkar

University of Utah

Materials & Systems Research, Inc.

122 S. Central Campus Drive Salt Lake City, UT 84112

Phone: 801/581-5396 Fax: 801/581-4816

E-mail: anil.virkar@m.cc.utah.edu

161. Steven J. Visco

Lawrence Berkeley National Laboratory

Materials Science Division

MS 62-247

Berkeley, CA 94720 Phone: 510/486-5821

Fax: 510/486-4881 E-mail: sjvisco@lbl.gov

162. Conghua Wang

University of Pennsylvania

3231 Walnut Street

Philadelphia, PA 19104

Phone: 215/898-8902 Fax: 215/573-2128

E-mail: cwang@lrsm.upenn.edu

163. David Weiss

Industrial Center

400 N. Capitol Street

Suite 400

Washington, DC 20001 Phone: 202/824-7153

Fax:

E-mail: dweiss@industrialcenter.org

164. Wendell R. Welch

USAF AEFB/DOC

360 Gunfighter Avenue

Suite 1

Mountain Home AFB, ID 83648

Phone: 208/828-3512 Fax: 208/828-3525

E-mail: wendell.welch@mountainhome.af.mil

165. Mark C. Williams

National Energy Technology Laboratory

U.S. Department of Energy 3610 Collins Ferry Road Morgantown, WV 26507-0880

Phone: 304/285-4747 Fax: 304/285-4216

E-mail: mark.williams@netl.doe.gov

166. Dennis Witmer

University of Alaska - Fairbanks

525 Duckering Buidling
Fairbanks, AK 99712
Phone: 907/474-7082
Fax: 907/474-6141
E-mail: ffdew@uaf.edu

167. Joseph A. Woerner

Analysis & Technology

301 Green Lee Road

Annapolis, MD 21402

Phone: 410/349-2035 Fax: 410/293-9690 E-mail: jwoerner@vrc.com

168. Richard Woods

Hydrogen Burner Technology, Inc.

3925 Vernon Street

Long Beach, CA 90815

Phone: 562/597-2442

Fax: 562/597-8780

E-mail: rwoods@hydrogenburner.com

169. Wayne L. Worrell

University of Pennsylvania

3231 Walnut Street

Philadelphia, PA 19104-6272

Phone: 215/898-8592

Fax: 215/573-2128

E-mail: worrell@seas.upenn.edu

170. John Wozniak

The Johns Hopkins University

Applied Physics Laboratory

11100 Johns Hopkins Road

Laurel, MD 20723-6099

Phone: 240/228-5744

Fax: 240/228-5512

E-mail: john.wozniak@jhuapl.edu

171. John Yamanis

Honeywell

101 Columbia Road

Morristown, NJ 07962-1021

Phone: 973/455-5052 Fax: 973/455-3008

E-mail: john.yamanis@honeywell.com

172. Edwin R. Yarbrough

Honeywell

1001 Pennsylvania Ave., N.W.

Suite 700 South

Washington, DC 20004
Phone: 202/662-2647
Fax: 202/662-2661

E-mail: ed.yarbrough@honeywell.com

173. Charles M. Zeh

National Energy Technology Laboratory U.S. Department of Energy 3610 Collins Ferry Road

Phone: 304/285-4265 Fax: 304/285-4469

Morgantown, WV 26507-0880

E-mail: charles.zeh@netl.doe.gov